G 5266 SCVi SF

Fully integrated dishwashers in standard size
42 dB I Cutlery tray I Comfort baskets I QuickIntenseWash I AutoOpen



- Tested for the equivalent of 20 years' service life*
- Flexible basket design perfect for everyday use – Comfort baskets
- QuickIntenseWash, superior cleaning and drying in under 60 min
- Completely dry – Miele AutoOpen drying
- Thanks to delay start, you can set a start time for the wash cycle up to 24 hours in advance
- Very easy door opening and closing – ComfortClose
- Clean Touch Steel front w/PureLine handle, fingerprint resistant

* During the development phase of the G 5000 and G 7000 dishwasher series, Miele tested models and core components in 5,600 wash cycles (= 280 wash cycles per year over a period of 20 years) in various programs. More at: mieleusa.com/20years

EAN: 4002516376163 / Material number: 11636750 /
Old Material Number: 21526663USA

General information	
Model number	G 5266 SCVi SF
Manufacturer material number	11636750
EAN number	4002516376163
Marketing class	Silver
Type	
Fully integrated dishwashers	•
24 inch dishwasher	•
Design	
Fascia color	Stainless Steel.
Fascia panel version	Fully integrated fascia
Control type	Program selector button
Control panel	7-segment display
Display color	Yellow
Convenience	
Door closing aid	ComfortClose
Operating noise dB(A) re 1 pW	42
Countdown indicator	•
Delay start up to 24 hours	•
In-operation indicator	acoustic
Efficiency	
Noise emissions in dB(A)	42
Proven hygiene	•
Hot water connection	•
Half load	•
Energy Star	•
Quality of results	
Fresh water dishwasher	•
AutoOpen drying	•
SensorDry	•
Water softener system	Uni. water softener to 70° dH, Economic salt consumption, Brilliant GlassCare
Active condensation drying	•
Perfect GlassCare	•
Wash programs	
QuickIntenseWash	•
Normal	•
Pots & Pans	•
SaniWash	•
Rinse & Hold	•
Dishwashing options	
Short	•
Express	•
Extra Clean	•
Extra dry	•

Miele

G 5266 SCVi SF
Fully integrated dishwashers in standard size
42 dB | Cutlery tray | Comfort baskets | QuickIntenseWash | AutoOpen



EAN: 4002516376163 / Material number: 11636750 /
Old Material Number: 21526663USA

Baskets	
Cutlery loading	3D MultiFlex Tray
FlexCare cup rack	1
Basket design	Comfort
Technical data	
Niche width min in in.(mm)	23 5/8 (600)
Niche width max in in.(mm)	23 5/8 (600)
Niche height min in in.(mm)	33 3/4 (855)
Niche height max in in.(mm)	36 1/4 (920)
Niche depth in in.(mm)	22 1/2 (570)
Appliance width in in.(mm)	23 5/8 (598)
Appliance height in in.(mm)	33 3/4 (855)
Appliance depth in in.(mm)	21 3/4 (550)
Appliance depth with door open in in.(cm)	47 1/2 (120.5)
Net weight in lbs. (kg)	111 (50.0)
Total connected load in kW	1.40
Voltage in V	120
Fuse rating in A	15
Number of phases	1
Electrical frequency standard	60
Length of water inlet hose in m	5 (1.50)
Length of water drain hose in m	5 (1.50)
Length of electrical wire in ft (m)	6 (1.70)
Min. front panel weight in kg	4.0
Max. front panel weight in kg	11.0
[can be retrofitted by Service to min.]	7.0
[can be retrofitted by Service to max.]	14.0
Standard accessories	
Voucher for 1 x box of UltraTabs (20 tabs) or 3 boxes (60 tabs in each) at a reduced price	•