G 5056 SCVi SF

Fully integrated dishwashers in standard size

44 dB I Cutlery tray I Comfort baskets I QuickIntenseWash I Delay start



- More flexibility and space for your dishware – height-adjustable upper basket
- Flexible basket design perfect for everyday use – Comfort baskets
- QuickIntenseWash, superior cleaning and drying in under 60 min
- Thanks to delay start, you can set a start time for the wash cycle up to 24 hours in advance
- Very easy door opening and closing – ComfortClose
- Clean Touch Steel front w/PureLine handle, fingerprint resistant

EAN: 4002516397687 / Material number: 11695330 /
Old Material Number: 21505663USA

General information	
Model number	G 5056 SCVi SF
Manufacturer material number	11695330
EAN number	4002516397687
Marketing class	Silver
Type	
Fully integrated dishwashers	•
24 inch dishwasher	•
Design	
Fascia color	Stainless Steel.
Fascia panel version	Fully integrated fascia
Control type	Program selector button
Control panel	7-segment display
Display color	Yellow
Convenience	
Door closing aid	ComfortClose
Operating noise dB(A) re 1 pW	44
Countdown indicator	•
Delay start up to 24 hours	•
In-operation indicator	acoustic
Efficiency	
Noise emissions in dB(A)	44
Proven hygiene	•
Hot water connection	•
Half load	•
Energy Star	•
Quality of results	
Fresh water dishwasher	•
Wash programs	
QuickIntenseWash	•
Normal	•
Pots & Pans	•
SaniWash	•
Rinse & Hold	•
Dishwashing options	
Short	•
Express	•
Extra Clean	•
Extra dry	•
Baskets	
Cutlery loading	Cutlery tray
FlexCare cup rack	1
Basket design	Comfort
Technical data	
Niche width min in in.(mm)	23 5/8 (600)
Niche width max in in.(mm)	23 5/8 (600)
Niche height min in in.(mm)	33 3/4 (855)
Niche height max in in.(mm)	36 1/4 (920)

G 5056 SCVi SF
Fully integrated dishwashers in standard size
44 dB I Cutlery tray I Comfort baskets I QuickIntenseWash I Delay start



EAN: 4002516397687 / Material number: 11695330 /
Old Material Number: 21505663USA

Niche depth in in.(mm)	22 1/2 (570)
Appliance width in in.(mm)	23 5/8 (598)
Appliance height in in.(mm)	33 3/4 (855)
Appliance depth in in.(mm)	21 3/4 (550)
Appliance depth with door open in in.(cm)	47 1/2 (120.5)
Net weight in lbs. (kg)	111 (50.0)
Total connected load in kW	1.40
Voltage in V	120
Fuse rating in A	15
Number of phases	1
Electrical frequency standard	60
Length of water inlet hose in m	5 (1.50)
Length of water drain hose in m	5 (1.50)
Length of electrical wire in ft (m)	4 (1.20)
Min. front panel weight in kg	4.0
Max. front panel weight in kg	11.0
[can be retrofitted by Service to min.]	7.0
[can be retrofitted by Service to max.]	14.0
Standard accessories	
Voucher for 1 x box of UltraTabs (20 tabs) or 3 boxes (60 tabs in each) at a reduced price	•