F 2672 Vi
24" MasterCool freezer
For high-end design and technology on a large scale.



- Push2open for convenient door-opening assistance
- Light floods the interior thanks to LED elements – BrilliantLight
- Ice and cooled-water dispensers for maximum convenience
- Convenient control thanks to color touch display MasterSensor

EAN: 4002516323143 / Material number: 11503550 /
Old Material Number: 37267201USA

General information	
Model number	F 2672 Vi
Manufacturer material number	11503550
EAN number	4002516323143
Marketing class	Diamond
Appliance category	
Freezer	•
Design	
Built-in	•
Built-in integrated	•
Door hinge side	Left
Can be installed side-by-side	•
Design	
Lighting	BrilliantLight
User convenience	
Networking with Miele@home	•
NoFrost	•
SoftClose door closing damper	•
IceMaker with mains water connection	•
Ice/Water dispenser with plumbed water connection	•
Push2open	•
FullAccess	•
EasyClean	•
MaxLoad hinge	•
Smart Extras	
Push notifications	•
Cooling tips	•
Cooling modes	•
IceMaker	•
Smart Extras	
RemoteUpdate	•
Smart Home Integration	•
Control	
Electronic temperature display and control	MasterSensor
SuperFrost	•
No. of temperature zones	1
Sabbath mode	•
Eco mode	•
Freezer/freezer zone	
Number of shelves	2
Number of freezer baskets	2
Door baskets – small	1
Door baskets – large	3
Efficiency	
Energy Star Qualified	•
Safety	
Lock function	•
Acoustic door alarm	•


F 2672 Vi
24" MasterCool freezer
For high-end design and technology on a large scale.



EAN: 4002516323143 / Material number: 11503550 /
Old Material Number: 37267201USA


Acoustic temperature alarm, freezer section	•
Optical door alarm	•
Optical temperature alarm	•
Technical data	
Niche width in inches (mm), min.	24 1/8 (610)
Niche width in inches (mm), max.	24 1/8 (610)
Niche height in inches (mm), min.	84 1/8 (2134)
Niche height in inches (mm), max.	84 1/8 (2134)
Niche depth in in.(mm)	24 7/8 (629)
Appliance width in in.(mm)	23 3/4 (603)
Appliance height in in.(mm)	83 5/8 (2125)
Appliance depth in in.(mm)	23 7/8 (608)
Weight in lbs.(kg)	316 (143.3)
Type of mounting	Fixed door
Maximum fridge compartment door front weight in lbs. (kg)	150 (68)
4-star freezer compartment volume in cu. ft. (l)	11.23 (318)
Storage time in case of fault in h	10
Sound emissions in dB(A) re 1 pW	42
Current consumption in milliampere (mA)	4000
Voltage in V	110 - 120
Fuse rating in A	10
Number of phases	1
Frequency in Hz	60
Wire length in ft (m)	9.8 (3.0)
Replacing bulbs	Customer Service
Available display languages	
Available display languages via MultiLingua	□□□□□□□□, □□, □□□□, deutsch, dansk, english, english (AU), english (CA), english (GB), english (US), eesti, suomi, français, français (CA), français (FR), ελληνικά, italiano, □□□, □□□, hrvatski, latviesu, lietuviu, bahasa malaysia, nederlands, norsk, polski, português, română, русский, svenska, srpski, slovenčina, slovenščina, español, čeština, türkçe, українська, magyar

F 2672 Vi
24" MasterCool freezer
For high-end design and technology on a large scale.




Side-by-side, MasterCool, without partition wall, with heating mat (Sketch) (with footnote)


1) Heating mat KSK 2001 (EU, AUS, CN) or KSK 2002 (US, CA, MX, BR)



F2672Vi, F2662Vi, F2671Vi, F2661Vi, installation, MasterCool (installation drawings)




Sideview, MasterCool, Sketch




Side-by-Side, MasterCool, footnote, installation drawings

1. KSK 2001/2002, 2. Device A, 3. Device B, A = niche device A, B = niche device B



KFP2445ed/cs, KFP2444ed/cs, Front panel, Front dimensions, MasterCool, installation drawings



F2672Vi, F2672SF, F2662Vi, F2671Vi, F2671SF, F2661Vi, MasterCool, installation, installation drawings

1. View from the front, 2. Mains Connection cable, L = 3000 mm (118 inch), 3. Water inlet positon, L = 2000mm (not for KON USA), 4. No water/ELT conections permitted in this area