F 2472 Vi
18" MasterCool freezer
For high-end design and technology on a large scale.



- Push2open for convenient door-opening assistance
- Light floods the interior thanks to LED elements – BrilliantLight
- Ice and cooled-water dispensers for maximum convenience
- Convenient control thanks to color touch display MasterSensor

EAN: 4002516323051 / Material number: 11503430 /
Old Material Number: 37247201USA

| | |
|---|---|
| **General information** | |
| Model number | F 2472 Vi |
| Manufacturer material number | 11503430 |
| EAN number | 4002516323051 |
| Marketing class | Diamond |
| **Appliance category** | |
| Freezer | • |
| **Design** | |
| Built-in | • |
| Built-in integrated | • |
| Door hinge side | Left |
| Can be installed side-by-side | • |
| **Design** | |
| Lighting | BrilliantLight |
| **User convenience** | |
| Networking with Miele@home | • |
| NoFrost | • |
| SoftClose door closing damper | • |
| Ice/Water dispenser with plumbed water connection | • |
| Push2open | • |
| FullAccess | • |
| EasyClean | • |
| MaxLoad hinge | • |
| **Smart Extras** | |
| Push notifications | • |
| Cooling tips | • |
| Cooling modes | • |
| **Smart Extras** | |
| RemoteUpdate | • |
| Smart Home Integration | • |
| **Control** | |
| Electronic temperature display and control | MasterSensor |
| SuperFrost | • |
| No. of temperature zones | 1 |
| Sabbath mode | • |
| Eco mode | • |
| **Freezer/freezer zone** | |
| Number of shelves | 2 |
| Number of freezer baskets | 2 |
| Door baskets – small | 1 |
| Door baskets – large | 3 |
| **Efficiency** | |
| Energy Star Qualified | • |
| **Safety** | |
| Lock function | • |
| Acoustic door alarm | • |
| Acoustic temperature alarm, freezer section | • |
| Optical door alarm | • |


F 2472 Vi
18" MasterCool freezer
For high-end design and technology on a large scale.



EAN: 4002516323051 / Material number: 11503430 /
Old Material Number: 37247201USA


| | |
|---|---|
| Optical temperature alarm | • |
| **Technical data** | |
| Niche width in inches (mm), min. | 18 (457) |
| Niche width in inches (mm), max. | 18 (457) |
| Niche height in inches (mm), min. | 84 1/8 (2134) |
| Niche height in inches (mm), max. | 84 1/8 (2134) |
| Niche depth in in.(mm) | 24 7/8 (629) |
| Appliance width in in.(mm) | 17 3/4 (451) |
| Appliance height in in.(mm) | 83 5/8 (2125) |
| Appliance depth in in.(mm) | 23 7/8 (608) |
| Weight in lbs.(kg) | 283 (128.1) |
| Type of mounting | Fixed door |
| Maximum fridge compartment door front weight in lbs. (kg) | 157 (71) |
| 4-star freezer compartment volume in cu. ft. (l) | 7.73 (219) |
| Sound emissions in dB(A) re 1 pW | 42 |
| Current consumption in milliampere (mA) | 4000 |
| Voltage in V | 110 - 120 |
| Fuse rating in A | 10 |
| Number of phases | 1 |
| Frequency in Hz | 60 |
| Wire length in ft (m) | 9.8 (3.0) |
| Replacing bulbs | Customer Service |
| **Available display languages** | |
| Available display languages via MultiLingua | □□□□□□□, □□, □□□□, deutsch, dansk, english, english (AU), english (CA), english (GB), english (US), eesti, suomi, français, français (CA), français (FR), ελληνικά, italiano, □□□, □□□, hrvatski, latviesu, lietuviu, bahasa malaysia, nederlands, norsk, polski, português, română, русский, svenska, srpski, slovenčina, slovenščina, español, čeština, türkçe, українська, magyar |

F 2472 Vi
18" MasterCool freezer
For high-end design and technology on a large scale.





Side-by-side, MasterCool, without partition wall, with heating mat (Sketch) (with footnote)


1) Heating mat KSK 2001 (EU, AUS, CN) or KSK 2002 (US, CA, MX, BR)




F2462Vi, F2472Vi, F2461Vi, F2471Vi, MasterCool, installation, installation drawings (US, CA)





Sideview, MasterCool, Sketch





Side-by-Side, MasterCool, footnote, installation drawings

1. KSK 2001/2002, 2. Device A, 3. Device B, A = niche device A, B = niche device B




KFP1845ed/cs, KFP1844ed/cs, MasterCool, Front panel, Front dimensions, sketch (US, CA)





F2413Vi, F2471Vi, F2471SF, F2461Vi, F2411Vi, F2411SF, installation, MasterCool, installation drawings

1. View from the front, 2. Mains Connection cable, L = 3000 mm (118 inch), 3. Water inlet positon, L = 2000 mm (not for KON USA), 4. No water/ELT conections permitted in this area

F 2472 Vi
18" MasterCool freezer
For high-end design and technology on a large scale.

[mm]




Opening angle 90°/115°, right side stop, MasterCool (Sketch) with footnote

A) Appliance door , F 2411 Vi: 525 mm (20 2/3 inch);, F 2412 Vi, F 2412 SF, F 2413Vi, F 2472 Vi, F 2472 SF: 525 mm (20 2/3 inch);, F 2671 Vi: 677 mm (26 2/3 inch); , F 2672 Vi, F 2672 SF: 677 mm (26 2/3 inch);, F 2812 SF, F 2812 Vi, F 2813 Vi: 829 mm (32 2/3 inch);, F 2912 Vi, F 2912 SF: 982 mm (38 2/3 inch);, B) Furniture front (max. 38 mm) (1 1/2 inch), C) Door handle, D) Distance from the door to the wall (without furniture front and door handle): , F 2411 Vi: 237 mm (9 1/3 inch);, F 2412 Vi, F 2412 SF, F 2472 Vi, F 2472 SF: 237 mm (9 1/3 inch);, F 2672 Vi, F 2672 SF: 296 mm (11 2/3 inch);, F 2811 Vi: 363 mm (14 1/3 inch);, F 2812 SF, F 2812 Vi: 363 mm (14 1/3 inch);, F 2912 Vi, F 2912 SF: 428 mm (16 7/8 inch);, E) ONLY valid for SF versions: A + 25 mm (1 inch)