DA 2518

Insert ventilation hood

with energy-efficient LED lighting and backlit controls for easy use.



- Customized kitchen design – fully integrated in 43 3/8 (1102) in (mm) width
- Unique user convenience – Con@ctivity
- Powerful – 500.29 (850) ft³/min (m3/h) in Booster level
- Efficient filtration- 10-ply stainless steel grease filters
- Safe and easy to clean – Miele CleanCover

EAN: 4002516024699 / Material number: 10876740 /
Old Material Number: 28251855USA

General information	
Model number	DA 2518
Manufacturer material number	10876740
EAN number	4002516024699
Marketing class	Gold
Design	
Insert ventilation hood	•
Construction type and design	
Color	Stainless steel
Operating modes	
Recirculated mode	Can be retrofitted
Recirculation conversion kit (order separately)	DUU 151
OdorFree charcoal filter (order separately)	DKF 15-P
User convenience	
Miele@home	•
Electronic controls	•
Con@ctivity	Yes
Power levels (number excl. Intensive)	3
Operation	Light-touch switches with LEDs
Booster levels	1
Delayed shutdown for 5 or 15 minutes	•
Grease filter saturation indicator	•
Active charcoal filter saturation indicator	•
CleanCover	•
Smart Extras	
RemoteUpdate	•
Push notifications	•
Smart Home Integration	•
Smart Extras	
Alexa voice control	•
Google voice control	•
Filter system	
Number of dishwasher-safe stainless steel grease filters (10-ply)	3
Lighting	
Number x W	4 x 3 W
Light intensity in Lx	520 lx
Color temperature in K	3000 Kelvin
Blower	
Dual-action blower	•
Exhaust air	
Air throughput in CFM in Booster	500
Air throughput with Booster level 1 (m³/h) according to EN 61591	500.29 (850)
Safety	
Safety shut-off	•

DA 2518
Insert ventilation hood
with energy-efficient LED lighting and backlit controls for easy use.



EAN: 4002516024699 / Material number: 10876740 /
Old Material Number: 28251855USA

Technical data	
Canopy width in in. (mm)	43 3/8 (1102)
Canopy height in in. (mm)	2 (50)
Electrical plug	NEMA plug: 5–15
Net weight in lbs. (kg)	32 (14.3)
Depth of hood canopy in in. (mm)	15 7/8 (402)
Length of electrical wire in ft (m)	2 (0.8)
Standard plug fitted	•
Minimum height above electric cooktops in mm	24 (610)
Minimum safety distance above gas cooktops (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	26 (660)
Total connected load in kW	0.36
Voltage in V	120
Fuse rating in A	15
Number of phases	1
Frequency in Hz	60
Installation note	
Vent connection at top	•
Diameter of vent connection in in.(mm)	6 (150)
Standard accessories	
Non-return flap	•