

#### **SRT364C**



### **FEATURES**

Maintain control with four dual-stacked burners that go from 20,000 Btu down to a mere breath of flame

Simmer and melt sauces, soups, and marinades easily with the lower tier of the dual-stacked burner

Match other Sub-Zero, Wolf, and Cove products with heavy-gauge stainless steel and signature red infinite control knobs

Sear with a 16,000 Btu infrared charbroiler

Cleanup is a snap as sealed, seamless burner pans contain sloshes and spills

Move pots and pans effortlessly across the continuous cast-iron grates

Reignites flame automatically with spark ignition system

### **ACCESSORIES**

2-Burner Wok Grate

Black Knobs

Filler Trim

Red Knobs

Stainless Steel Knobs

Stainless steel, brass or chrome bezels

High altitude conversion kits available

5" and 10" stainless steel risers, and 20" riser with shelf

Accessories available through an authorized dealer. For local dealer information, visit <u>subzero-wolf.com/locator</u>.










### **TOP CONFIGURATION**



# RANGETOP SPECIFICATIONS

- · Stainless-steel island trim (included)
- Stainless-steel bezels
- 1 9,200 Btu burner
- 1 15,000 Btu burner
- 1 18,000 Btu burner
- 1 20,000 Btu burner
- 1- Infared 16,000 Btu charbroiler




#### PRODUCT SPECIFICATIONS

Model	SRT364C		
Dimensions	35 7/8"W x 8 1/2"H x 28 1/2"D		
Electrical Supply	120 VAC, 60 Hz		
Electrical Service	15 amp dedicated circuit		
Gas Supply	3/4" ID line		
Gas Inlet	1/2" NPT female		
Receptacle	3-prong grounding-type		


# **ELECTRICAL**

### GAS




NOTE: Dimensions in parenthesis are in millimeters unless otherwise specified

### **DIMENSIONS**



#### STANDARD INSTALLATION



\*Without ventilation hood, 36" (914) minimum clearance countertop to combustible materials, 44" (118) for charbroiler.

NOTE: Shaded area above countertop indicates minimum clearance to combustible surfaces,

combustible materials cannot be located within this area. Electrical and gas supply located through bottom of platform.

For island installation, 12" (305) minimum clearance back of range to combustible rear wall above countertop.