TV4 & DV4


COMMERCIAL THROUGH RETAIL
COIN SLIDE
TOP LOAD WASHER
& MATCHING DRYER

Built for Reliable Performance

Speed Queen® coin slide operated top load washer and matching dryer combine heavy-duty construction with reliable operation proven to stand the test of time. With features such as water and energy efficient designs, quality internal components and high security systems, owners can depend on Speed Queen.



TV4 Control Panel



DV4 Control Panel

Washer:

- Durable stainless steel wash tub
- Extract speed of 710 RPM spins clothes out drier
- Automatic Balancing Suspension provides the industry's best out-of-balance handling, completing wash cycles without interruption
- Curved four-vane polypropylene agitator provides 210° agitation stroke which delivers superior washability

Dryer:

- Door is reversible for installation flexibility
- High efficiency exhaust blower with superior airflow 220 cfm (105 liters/sec)
- 100% serviceable from the front
- Efficient and fast dry cycle



COMMERCIAL THROUGH RETAIL
COIN SLIDE
TOP LOAD WASHER & MATCHING DRYER





TV4

Product Code		TV4000WN
Control Option		Coin Slide
Color		White
Capacity - lb (kg)		14 (6.3)
Cylinder Volume - cu.ft. (liters)		3.19 (90.3)
Spin Speed G-Force (RPM)		150 (710)
Motor Size - HP (kw)		0.5 (0.37)
Water Consumption Per Cycle - g (liter)*		28.07 (106)
IWF (Water Factor) - gal/ft³ (liters/liter/cycle)*		8.8 (1.18)
MEF_{J2} (Modified Energy Factor) ft³/kWh/cycle (Liters/kWh/cycle)*		1.35 (38.2)
Cycle Selections		Normal Hot, Normal Warm, Normal Cold, Delicate, Perm Press Cold, Perm Press Warm
Electrical Requirements (v/Hz/Ph-Amp)		120/60/1 - 15 Amp
Water Pressure - p.s.i (bar)		20-120 (1.4/8.3)
Drain		Pump
Cylinder Finish		Stainless Steel
Net Weight - lb (kg)		206 (93)
Shipping Weight - lb (kg)		214 (97)
Shipping Dimensions Approx. - in	Width	28.25
	Depth	30
	Height	45
Agency Approvals		cULus
Model No.		SWNSX2SP115TW02

DV4

Product Code		Gas: DV4000WG Electric: DV4000WE
Control Option		Coin Slide
Color		White
Capacity - lb (kg)		18 (8.2)
Cylinder Volume - cu.ft. (liters)		7.0 (198)
Motor (Thermal Protected)		0.33 HP
Type of Gas (Gas Models Only)		Factory Equipped Natural
Air Outlet Diameter - in		4
Exhaust Airflow - cfm (liters/sec)		220 (105)
Cycle Selections		Normal, Perm Press, Delicate, No Heat
Electrical Requirements	**Electric	120/208/240/60/1-30 Amp
	Gas	120/60/1-15 Amp
Heating Element	Electric	5350W, 240V / 4750W, 208V
	Gas	25,000 Btu
Net Weight - lb (kg)		150 (68)
Shipping Weight - lb (kg)		161 (73)
Shipping Dimensions Approx. - in	Width	30.5
	Depth	29.5
	Height	45
Agency Approvals		cULus
Model No.		SDESXRGS173TW01 SDGSXRGS113TW01

Dimensions	Width - in	Height - in	Depth - in	Floor to Door Opening - in	Door Swing - in
TV4000WN	25.625	43.875	28	51	–
DV4000WE/DV4000WG	26.875	43.875	28	15.44	23.5

Required Coin Kits *(sold separately)*
Coin Slide kit – Model #: CK124

For Commercial Use Only

* Average usage based on multiple load sizes and current DOE test protocol. Real usage will vary depending on load size, composition and cycle selectivity.
** Electric dryers are dual rated for 208-240V applications. Using dryer in 208V will reduce the wattage output.
An optional kit (61928) can be used to field convert the unit for 4750 output at 208V.
Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management systems of Alliance Laundry Systems are registered to ISO 9001.

AR23-0087
Speed Queen by Alliance Laundry Systems