FRIGIDAIRE PROFESSIONAL



36" Electric Cooktop

Electric Cooktop

Available Products: PCCE3680AF

Available Colors: Stainless Steel

Version: 10/25

Product Specifications

Cooktop

Bridge Element	Yes
Bridge Element Location	Left
Cooking Surface Type	Smooth
Hot-Surface Indicator Light	Yes

Display

Display Type	Mechanical

Electrical Specifications

Connected Load @ 240V	8.1 kW
Minimum Circuit Required	40 Amps
Voltage Rating	240 V

General Specifications

Frigidaire Fit Promise	Yes
Prop 65 Label	Yes
Warranty - Labor	1 Year
Warranty - Parts	1 Year

Safety Certifications and Approvals

CSA Listed	Yes
UL Listed	Yes

Cooktop Performance

Right Front Element Burner Size	9"
Left Front Element Burner Size	7"
Left Rear Element Burner Size	7"
Center Front Element Burner Size	6"
Right Front Element Burner	3200 Watts
Left Front Element Burner	1800 Watts
Left Rear Element Burner	1800 Watts
Center Front Element Burner	1200 Watts
Center Rear Element Burner	100 Watts
Keep Warm Burner Location	Center Rear

Dimensions and Volume

Height	2 5/8"
Width	36 3/4"
Depth	21 3/8"
Cutout Height	5"
Minimum Cutout Width	33 7/8"
Minimum Cutout Depth	19 1/8"
Maximum Cutout Width	36 1/8"
Maximum Cutout Depth	20 1/2"

Installation

Installed Over a Wall Oven	Yes

Certifications and Approvals

ADA Compliant	Yes

Right to Repair Details


Right to Repair	Available - Visit frigidaire.ca/right-to-repair for more information

For planning purposes only. We reserve the right to change specifications or discontinue models without notice.
Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.ca
Electrolux Major Appliances, N.A.
CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • frigidaire.ca

36" Electric Cooktop	5485
Available Products: PCCE3680AF	Available Colors: Stainless Steel
Version: 10/25	

Installation Diagram


Cooktop Dimensions



IMPORTANT INSTALLATION-INFORMATION

- All electric cooktops run off a single phase, three-wire or four-wire cable, 240/208 volt, 60 hertz, AC only electrical supply with ground.
- Please note minimum distances between cooktop and adjacent and overhead cabinetry is 30" (76.2cm).

Cooktop Cutout Dimensions



* 30" (76.2 cm) min. for unprotected cabinet
24" (61 cm) min. for protected surface

Figure 1

MODEL	A. LENGTH	B. WIDTH	C. DEPTH	CUTOUT DIMENSIONS D. LENGTH MIN.	CUTOUT DIMENSIONS D. LENGTH MAX.	CUTOUT DIMENSIONS E. WIDTH MIN.	CUTOUT DIMENSIONS E. WIDTH MAX.	F. DEPTH BELOW COOKTOP*
30"	30 5/8" (77.8 cm)	21 3/8" (54.4 cm)	2 5/8" (6.7 cm)	28 1/2" (72.4 cm)	29 7/8" (75.9 cm)	19 5/8" (49.9 cm)	20 1/2" (52.1 cm)	5" (12.7 cm)
36"	36 3/4" (93.5 cm)	21 3/8" (54.4 cm)	2 5/8" (6.7 cm)	33 7/8" (86.0 cm)	36 1/8" (91.8 cm)	19 1/8" (48.6 cm)	20 1/2" (52.1 cm)	5" (12.7 cm)

For planning purposes only. We reserve the right to change specifications or discontinue models without notice.
Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.ca
Electrolux Major Appliances, N.A.
CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • frigidaire.ca