UP48N



Colour range
Body

- Blue grey – BG
- Antique white – AW
- White – WH
- Blue – MB
- Stainless steel – SS
- Graphite matt – MG
- Glossy black – BK
- Burgundy red – BU
- Emerald green – EG
- Optional RAL – RA + $ 2800.00

Finishes
Knobs, handles, frames (optional)

- Brass – G
- Copper – P
- Chrome – C
- Burnished – B

Optional solid door version
optional + $ 700.00

Order code: add letter “Q” before the “N” letter

Noblesse frames
optional → p. 138




Available ovens

Electric oven

Primary oven:
UOV 80 M
Maximum input:
3.7 kW

Secondary oven:
UOV 30 E
Maximum input:
2.5 kW

Configurations

	5 burners with fry top* and coup de feu	8 burners with fry top*	Induction
			
Electric oven	UP48FSNMP	UP48FNMP	UPI486NMP
	Brass/Copper/Chrome/Burnished	Brass/Copper/Chrome/Burnished	Brass/Copper/Chrome/Burnished
	$ 10.990.00	$ 9.990.00	$ 10.990.00
Fuel requirements	Natural gas / Liquid propane Voltage: 240 Volts Amps: 25.8	Natural gas / Liquid propane Voltage: 240 Volts Amps: 25.8	All electric Voltage: 240 Volts Amps: 73.8

**Insufficient amperage may lower heating performance when multiple functions are being used at the same time*

Consumption

- Bridge induction zone Ø 7" 1/4 + Ø 7" 1/4 1.85 / 2.5 kW + 1.85 kW
- Induction zone Ø 5" 3/4 1.4 / 1.8 kW
- Induction zone Ø 7" 1/4 1.85 / 2.5 kW
- Induction zone Ø 8" 11/16 2.3 / 3.2 kW
- Coupe de Feu 5500 btu/h
- Double ring Dual burner 25000 btu/h / 900 btu/h
- Griddle 10500 btu/h / 2000 btu/h + 7000 btu/h / 1400 btu/h
- Oval burner 10500 btu/h / 3100 btu/h
- Big burner 10500 btu/h / 2000 btu/h
- Small burner 7000 btu/h / 1400 btu/h

Complements & accessories

Hood	UAG48	Hood	UANB48	Ladle holder panel	AM4-120
	$ 2.755.00	Brass/Copper/Chrome/Burnished	$ 5.929.00		$ 349.00

Technical drawing & dimensions

