### **PP7036DJ**

## GE Profile™ 36" Built-In Knob-Control Cooktop

### **DIMENSIONS AND INSTALLATION INFORMATION (IN INCHES)**


**IMPORTANT:** Requires a 5" free area between the bottom of the cooktop to any combustible material, i.e., shelving. Free area not required when installing wall oven underneath cooktop. Refer to installation instructions. Requires a 15" minimum from cooktop to adjacent overhead cabinets. Units are furnished with a 48" flexible armored cable.

NOTE: 36" Ribbon cooktops are approved for use over select GE 30" Single Wall Ovens and Warming Drawers. Refer to cooktop and wall oven/warming drawer installation instructions packed with product for current dimensional data. If installed with a GE Telescopic Downdraft System, consult both the cooktop and downdraft installation instructions packed with product before installing. Cooktop gas/electric supply may need to be re-routed to install downdraft. The countertop cutout requires 23-1/2" minimum flat countertop surface and 25" minimum total countertop depth. In addition, other clearances to front edge of the countertop must be considered.

Before installing, consult installation instructions packed with product for current dimensional data.

#### 13" MAX. depth of unprotected overhead cabinets (when no hood or microwave is installed) APPROXIMATE COOKING DIMENSIONS 3-1/4" at front of unit and v Cooktop 5-9/16" at conduit location 33-3/4" 19-1/8" to 19-1/4" 30" MIN. from countertop to 15" MIN. height from countertop unprotected cabinet (when to nearest cabinet (including no hood or microwave is light rails) on both sides of 33-7/8 1-3/4" MIN. installed) cooktop to rear wall See label next to nameplate for MIN. clearance to wall 2-1/2" MIN. Required Electrical junction box 16" MIN. below countertop 2" MIN. clearance To insure accuracy, it is best to make a to side wall from cut-out template when cutting the opening in the counter on both sides of cooktop

#### **INSTALLATION ABOVE A WALL OVEN**



VOLTAGE (60HZ AC)	240V	208V
CONNECTED LOAD (MAX.)	9.6kW	7.2kW
CURRENT DRAW (MAX.)	40.0 Amps	34.7 Amps
RECOMMENDED CIRCUIT BREAKER	40 Amps	40 Amps

\*NOTE: Check local codes for required breaker size.



For answers to your Monogram, GE Café™ Series, GE Profile™ Series or GE Appliances product questions, visit our website at geappliances.com or call GE Answer Center® Service, 800.626.2000.







## **PP7036DJ**

# GE Profile™ 36" Built-In Knob-Control Cooktop

#### **FEATURES AND BENEFITS**

Five radiant cooking elements

Power Boil tri-ring element

Power Boil dual-ring element

SyncBurners

Keep warm setting

Melt setting

Control lock capability


Red LED with black glass surface

Hot surface indicator lights

Cooktop "on" indicator light

Fit Guarantee

Model PP7036DJBB - Black on black



#### **GUARANTEED FIT**

Replacing a similar cooktop from GE Appliances or another brand? GE cooktops are guaranteed for an exact fit or GE Appliances will pay up to \$100 toward modifications

Visit geappliances.com for more info

