PRG366WG

36-INCH GAS PRO GRAND® RANGE



PROFESSIONAL COLLECTION, COMMERCIAL-DEPTH, PORCELAIN COOKTOP SURFACE










FEATURES & BENEFITS

- ExtraHigh Star® Burner provides 22,000 BTUs of power for searing or boiling with QuickClean Base® designed for easy surface cleaning
- ★ 4 ExtraLow® burners offer precision simmering, melting or keeping warm
 - Includes three Full Access $^{\scriptsize (\!0\!)}$ telescopic racks, all with an integrated easy-grip handle
 - Hydraulic SoftClose® hinges prevent slamming for ultra smooth closing
- Super Fast 2-hour self-clean mode is the fastest in the industry

TECHNICAL DETAILS				
Circuit Breaker	15 A			
Volts	120 V, 60Hz 3 Wire			
Energy Source	Gas			
Plug Type	120V-3 prong			
Power Cord Length	65" (1,651 mm)			
Gas Supply	3/4"			
WARRANTY				
Limited Warranty, Entire Appliance, Parts and Labor	2 Year			

SEE PAGE 2 FOR INCLUDED AND OPTIONAL ACCESSORIES

RANGETOP



Total Number of Cooktop Burners	6		
1 – Power of Back Left Burner BTU	15,000 and XLO		
2 – Power of Front Left Burner BTU	22,000 and XHI / XLO		
3 – Power of Back Center Burner BTU	15,000		
4 – Power of Front Center Burner BTU	18,000		
5 – Power of Back Right Burner BTU	15,000 and XLO		
6 – Power of Front Right Burner BTU	18,000 and XLO		

OVEN	
Oven Capacity	5.7 cu. ft.

Cooking Modes

Bake, Convection Bake, Roast, Broil, Keep Warm

Sabbath	Yes		
Self-Clean	Yes		
Telescopic Rack(s)	3		
Interior Lights	2		
Bake Power	23,700 BTU		
Broil Power	17,500 (Infrared) BTU		
Home Connect® (Wi-Fi Enabled)	Yes		
Cavity Interior Dimensions (HxWxD)	16 1/4 " x 28" x 21 1/2 "		
Cavity Usable Dimensions (HxWxD)	11 1/4" x 25 3/8" x 19 1/2"		

DIMENSIONS & WEIGHT	
Overall Appliance Dimensions (HxWxD)	35 3/4 " – 36 3/4 " × 35 15/16 " × 27 7/8 "
Required Cutout Size (HxWxD)	35 3/4 " – 36 3/4 " × 36" × 24" – 25 1/8 "
Net Weight	391 lbs.

Page 1 of 5 7 / 25

PRG366WG 36-INCH GAS PRO GRAND® RANGE



PROFESSIONAL COLLECTION, COMMERCIAL-DEPTH, PORCELAIN COOKTOP SURFACE

ACCESSORIES (INCLUDED)

3 Telescopic Racks, Multi-Point Meat Probe, Island Trim

ACCESSORIES (OPTIONAL)



PWOKRINGHC

Wok Ring



PAGRIDDLE

Professional Griddle, Sits on Top of Grates Over 2 Star Burners, High-Release Coating



PA36WTKG

Toekick



PALPKITGGW

LP Conversion Kit, Pro Grand Gas Models with 4 and 6 Burners



PA12CHPBLK

Chopping Block / Cutting Board



PA36WLBG

7" Low Backguard*



PARKB36GY

Metallic Blue Knob Kit

PAALTKITGW

High Altitude Kit, Natural Gas or Dual-Fuel Pro Grand Ranges, 5,400 ft. to 10,200 ft.

Contact Customer Support

High Altitude Kit, Gas or Dual-Fuel Pro Grand Ranges Connected to LP Gas, 10,000 ft. to 10,200 ft.


*Models PCG305xx, PRD305xx, PRD606xx, PRG305xx, PRG305xx, PRG304xx and PRD304xx are suitable for 0" rear clearance to combustible surfaces. All other models: when using the included Island Trim a minimum 6" (152 mm) rear clearance is required to a combustible surface. When installing against a combustible surface, a Thermador® Low Backguard is required for a 0" rear clearance to the combustible surface. A Thermador Low Backguard must be purchased separately. A rear clearance to a surface covered in a noncombustible material (metal, ceramic tile, brick, marble, or stone) is 0" when using the included Island Trim. Clearances of less than 6" (152 mm) should be approved by the local codes and/or by the local authority having jurisdiction. Clearances from non-combustible materials are not part of the ANSI Z21.1 scope and are not certified by CSA.

Page 2 of 5 7 / 25




PROFESSIONAL COLLECTION, COMMERCIAL-DEPTH, PORCELAIN COOKTOP SURFACE

36-INCH RANGE DIMENSIONS



36-INCH RANGE CUTOUT DIMENSIONS



Range model	Gas zone A	Electric zone B	Х	С	D	E
All Harmony series	4'' (102)	6'' (152)	5'' (127)	N/A	N/A	2'' (51)
36"/ 48" Grand series	4'' (102)	6'' (152)	8" (203)	4'' (102)	3'' (76)	2'' (51)
60" Grand series	4'' (102)	6'' (152)	8'' (203)	4'' (102)	3'' (76)	1'' (25)


Page 3 of 5 7 / 25



PROFESSIONAL COLLECTION, COMMERCIAL-DEPTH, PORCELAIN COOKTOP SURFACE

36-INCH RANGE DIMENSIONS AND CLEARANCE REQUIREMENTS WITH "LOW BACK"

NOTE: A 36-inch minimum clearance is required between the top of the cooking surface and the bottom of an unprotected cabinet. A 30-inch clearance can be used when the bottom of the wood or metal cabinet is protected by not less than 1/4 inch of a flame retardant material covered with not less than No. 28 MSG sheet steel, 0.015 inch (0.4 mm) thick stainless steel, 0.024 inch (0.6 mm) aluminum, or 0.020 inch (0.5 mm) thick copper.




 Λ As defined in the "National Fuel Gas Code" (ANSI Z223.1, Current Edition). Clearances from non-combustible materials are not part of the ANSI Z21.1 scope and are not certified by CSA. Clearances of less than 6" (152 mm) must be approved by the local codes and/or by the local authority having jurisdiction.

Page 4 of 5 7 / 25



PROFESSIONAL COLLECTION, COMMERCIAL-DEPTH, PORCELAIN COOKTOP SURFACE

36-INCH RANGE DIMENSIONS AND CLEARANCE REQUIREMENTS WITH "FLUSH ISLAND TRIM"



⚠ As defined in the "National Fuel Gas Code" (ANSI Z223.1, Current Edition). Clearances from non-combustible materials are not part of the ANSI Z21.1 scope and are not certified by CSA. Clearances of less than 6" (152 mm) must be approved by the local codes and/or by the local authority having jurisdiction.

These warranties give you specific legal rights and you may have other rights that vary from state to state. Limited warranty from date of delivery. For complete warranty details, refer to your Use & Care manual, or ask your dealer.

Specifications are for planning purposes only. Refer to installation instructions and consult your countertop supplier prior to making counter opening. Consult with a heating and ventilation engineer for your specific ventilation requirements. For the most detailed information, refer to installation instructions accompanying product or write to Thermador indicating the model number. Specifications are correct at time of printing. Thermador reserves the right to change product specifications or design without notice. Some models are certified for use in Canada. Thermador is not responsible for products that are transported from the U.S. for use in Canada.

 $1\,800\,735\,4328 \mid USA\,THERMADOR.COM\mid CANADA\,THERMADOR.CA\mid @2025\,BSH\,HOME\,APPLIANCES\,CORPORATION.\,ALL\,RIGHTS\,RESERVED.$

Page 5 of 5 7 / 25