

SYSTEM SPECIFICATION AND PERFORMANCE DATA SHEET

PureSource®3 Ice & Water Filter System

APPLICATION GUIDELINES / CONDITIONS OF USE

Water Supply	Municipal or well applications
Water Temp.	Max. 100°F (38°C), Min. 33°F (0.6°C) - For cold water use only
Water Pressure	100 psi (689 kPa) Max. 30 psi (207 kPa) Min., as measured at the valve inlet
<ul style="list-style-type: none"> Timely cartridge replacement is essential for the product to perform as advertised. Please refer to the Use & Care Manual for general operation and maintenance requirements. Your refrigerator will have an electronic light on the freezer door dispenser that lights up yellow or displays ORDER when it is almost time to replace the filter and lights up red or displays REPLACE when you must replace the filter. Press the indicator button for approximately 3-10 seconds to reset after replacing the filter cartridge. Please refer to the Use & Care Manual for complete instructions. Flush the new cartridge for 4 minutes. Do not use the PureSource®3 Ice & Water Filter System on water that is microbiologically unsafe or with water of unknown quality without adequate disinfection before or after the system. You may use the system on disinfected waters that may contain filterable cysts. While testing was performed under standard laboratory conditions, actual performance may vary. High sediment areas may require you to replace the filter cartridge more frequently. Spent absorption media will not be regenerated or used. The PureSource®3 Ice & Water Filter System will absorb bad tastes and odors in both ice cubes and drinking water. 	

SYSTEM SPECIFICATIONS


Flow Rate	Ice Maker - 3.4 to 4.3 oz (99 - 125 cc) per 6.3 seconds at 60 psi (as measured at valve inlet) Dispenser - 60 oz per minute (0.5 gpm or 1.9 liters per minute) at 60 psi (as measured at valve inlet)
Capacity	200 gallons (757 liters)
System Construction	Filter Housing Assembly - Polypropylene Plastic Water Storage Tank - Polyethylene Plastic Tubing - Polyethylene Plastic Filter Media - Extruded Carbon Block

REPLACEMENT CARTRIDGE INFORMATION

Replacement **WF3CB™** cartridges are available through your local Frigidaire dealer or by calling the Customer Assistance Center at 1-877-4ELECTROLUX (1-877-435-3287).
Please reference **INSTALLATION** in the Use & Care Manual for replacing the cartridge and warranty information. Estimated cost for the replacement filter cartridge kit: Less than \$40.00.

PERFORMANCE DATA

MODEL: **PureSource®3** Use the replacement cartridge listed below.

	The PureSource®3 system with the WF3CB™ cartridge has been tested according to NSF/ANSI Standard 42/53/401 for the reduction of substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standard 42/53/401.
--	---

General test water parameters; pH = 7.5 +/- 0.5 Temp. 20°C +/- 3°C (68°F +/- 5°F) Pressure = 60 psi

Substance Reduction	NSF Standard	NSF Reduction Requirements	Influent Challenge Concentration	Maximum Permissible Product Water Concentration	Average Percent Reduction	
Chlorine taste and odor	42	>/= 50%	2.0 ± 10% mg/L	n/a	97.40%	
Chlorobenzene	53	n/a		0.1 mg/L	99.90%	
Cysts		99.95%	Min 50,000/L	n/a	99.99%	
2,4-D (Herbicide)		n/a	0.210 ± 10% mg/L	0.07 mg/L	94.50%	
Alachlor			0.04 ± 10% mg/L	0.002 mg/L	97.50%	
Atrazine			0.009 ± 10% mg/L	0.003 mg/L	94.00%	
Lead			0.15 ± 10% mg/L	0.005 mg/L	99.10%	
Mercury			0.006 ± 10% mg/L	0.002 mg/L	80.40%	
Lindane			0.002 ± 10% mg/L	0.0002 mg/L	99.00%	
O-Dichlorobenzene			1.8 ± 10% mg/L	0.6 mg/L	99.90%	
Toxaphene (Pesticide)			0.015 ± 10% mg/L	0.003 mg/L	93.50%	
Particulate class I	42	>/= 85%	Min. 10,000 part/mL	>/= 85%	99.90%	
Turbidity	53	n/a	11 +/- NTU	0.5 NTU	98.50%	
Styrene			2.0 ± 10%	0.1 mg/L	99.90%	
Tetrachloroethylene			0.015 ± 10%	0.005 mg/L	99.60%	
Atenolol	401		200 ng/L ± 20%	30 ng/L	>95.3	
Ibuprofen			400 ng/L ± 20%	60 ng/L	>94.8	
Trimethoprim			140 ng/L ± 20%	20 ng/L	>96.6	
Microplastics, particles 0.5 to < 1 um		>/= 85%	Min 10,000 particles/ml	>/= 85%	99.9%	





This filter is certified by the Water Quality Association to
WQA/ASPE/ANSI-803 for sustainability.

Ce filtre est certifié par la Water Quality Association conformément à
la norme WQA/ASPE/ANSI-803 pour la durabilité.

Este filtro está certificado por la Water Quality Association según
WQA/ASPE/ANSI-803 por sostenibilidad.