FRIGIDAIRE.



7 Cu. Ft. Electric Dryer

Dryer

Available Products: FLVE7523BW

Available Colors: White

Version: 11/24

Product Specifications

Dryer		Dryer Cycles	
Drum Back Type	Stainless Steel	Cycle Count	10
Drum Material	Aluminized Alloy Steel	Active Wear	Yes
Dryness Level Selections	Yes	Air Fluff	Yes
Lint Filter	Yes	Bulky	Yes
Moisture Sensor	Yes	Casual	Yes
		Delicates	Yes
Dryer Options		Fast Dry	Yes
Child Lock	Yes	Heavy Duty	Yes
Damp Dry Signal	Yes	Normal	Yes
Time Adjust (Add Time)	Yes	Sanitize	Yes
Time Adjust (Remove Time)	Yes	Timed Dry Time	Yes
Wrinkle Care	Yes	-	
		Drying Temperatures	
Dryness Level		Air Fluff	Yes
Max	Yes	Low	Yes
Normal	Yes	Medium	Yes
More Dry	Yes	High	Yes
Less	Yes	Maximum	Yes
		_	
Exterior		Controls	
Reversible Door	Yes	Child Lock	Yes
T1 10		Dimensions and Volume	
Electrical Specifications	2.40	Height	43 1/10"
Voltage Rating	240v	Width	27"
- "		Depth	30 1/10"
Installation		Depth With Door 90° Open	50"
Ventilation Type	Vented	Dryer Drum Capacity	7 Cu. Ft.
		Dryer Druin Capacity	7 Gu. Ft.
Safety Certifications and Approvals	••	Energy Data	
CSA Listed	Yes	kWh/cycle	2.27 kWh
UL Listed	Yes	kWh/year	641 kWh
		it titll y car	OTLEVIII
		General Specifications	
		Chime On / Chime Off	Yes
		Leveling Legs	Yes
		Prop 65 Label	Yes
		Warranty - Labor	1 Year
		Warranty - Parts	

Available Products: FLVE7523BW Available Colors: White

Version: 11/24

Installation Diagram

Installation in a Recess or Closet

- A dryer installed in a bedroom, bathroom, recess or closet, MUST be exhausted outdoors.
- 2 No other fuel burning appliance shall be installed in the same closet as the gas dryer.
- 3 Your dryer needs the space around it for proper ventilation.

DO NOT install your dryer in a closet with a solid door.

4 Closet door ventilation required: A minimum of 120 square inches (774.2 cm²) of opening, equally divided at the top and bottom of the door, is required. Openings should be located 3 inches (7.6 cm) from bottom and top of door. Openings are required to be unobstructed when a door is installed. A louvered door with equivalent air openings for the full length of the door is acceptable.

Dryer Dimensions









