



### **Features and Benefits**

## Design

- Black porcelain-enameled cooking surface
- Low-profile design for an integrated appearance
- Heavy-duty metal knobs for a premium look and feel
- Superior quality stainless steel exterior finish

#### Performance

• Dual flame ring power burner

### Convenience

- 5 Burners add flexibility to your cooking
- . Heavy-duty grates can be cleaned in dishwasher
- Oven light to better monitor cooking progress
- Kitchen timer
- Extra large door window for easy monitoring of cooking process
- LP conversion kit included for conversion from natural gas to liquid propane

# Capacity

• Capacity at 3.7 Cu Ft.

Notes: All height, width and depth dimensions are shown in inches. \*Please refer to installation instructions prior to making cutout. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details. Applicable product warranty can be foundin a ccompanying product literature or you may contact your account manager for further details.



Total number of cooktop burners	5
Cooking mode	Circulating air, Gas
Cooking mode	bottom heating,
	Gas grill/broiler
Integrated Cleaning system	Catalytic partial
Oven Control	mechanical
Knob Material	Full metal
Included accessories	i dii illotai
Sealed Burners	Yes
Number of Double grates	2
Bake Element Wattages primary cavity (W)	
Broil Element Wattages primary cavity (W)	
Convection Element Wattages primary	
cavity (W)	
Number of gas burners	5
Location of 1st heating element	front left
Power of 1st burner (BTU)	5000
Location of 2nd heating element	center left
Power of 2nd burner (BTU)	ounter left
Location of 3rd heating element	back left
Power of 3rd burner (BTU)	10000
Location of 4th heating element	middle back
Power of 4th burner (BTU)	IIIIddie back
Location of 5th heating element	back right
Power of 5th burner (BTU)	5000
Location of 6th heating element	center right
Power of 6th burner (BTU)	Center right
Power of griddle element	
Display	
Safety device	Safety valve
Salety device	Salety valve
Technical Specification	
UPC code	825225960935
Product color	
Gas type	Natural gas 15
	mbar (USA)
Alternative gas type	. ,
Total BTU load	76500
Total BTO load	
Watts (W)	
	15
Watts (W)	15 120
Watts (W) Current (A) Volts (V)	
Watts (W) Current (A) Volts (V) Frequency (Hz)	120
Watts (W) Current (A) Volts (V)	120 60 ETL
Watts (W) Current (A) Volts (V) Frequency (Hz) Approval certificates	120 60 ETL 30" width slide-in
Watts (W) Current (A) Volts (V) Frequency (Hz)	120 60 ETL 30" width slide-in 36" x 29 15/16"
Watts (W) Current (A) Volts (V) Frequency (Hz) Approval certificates	120 60 ETL 30" width slide-in

Notes: All height, width and depth dimensions are shown in inches. \*Please refer to installation instructions prior to making cutout. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details. Applicable product warranty can be foundin a ccompanying product literature or you may contact your account manager for further details.

For more information on our entire line of products, go to boschappliances.com or call 1-800-944-2904.

Copyright ©2020 BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch GmbH.

Litho Date: 09/2020