



Vario 200 series induction cooktop VI 263

VI 263 620

Black aluminum control panel.
Width 24" (60 cm).

Included accessories

1 glass scraper.

Installation accessories

VV 200 010

Stainless steel connection strip for combination with other Vario 200 series appliances.

VV 200 020

Black connection strip for combination with other Vario 200 series appliances.

Optional accessories

Part #17006018

Stainless steel frying sensor pan.
Non-stick cooking, ø 6".

Part #17006184

Stainless steel frying sensor pan.
Non-stick coating, ø 7".

Part #17006185

Stainless steel frying sensor pan.
Non-stick coating, ø 8".

Part #17006019

Stainless steel frying sensor pan.
Non-stick coating, ø 11".

VD 200 020 (requires two)

Vario 200 Series black appliance cover.

Combinable with:

2x VL 200 120
AW 442 720
AI 230 700
AW 230 790
AF 210 791

Good to know:

Wall installations require the hood to be as large as the cooktop(s). Island installations require the hood to be larger than the cooktop(s).

Highlights

- Can be combined with other Vario 200 series products.
- Control panel for comfortable and secure operation.

Cooking zones

3 cooking zones:

1 induction cooking zone 11" (2,600 W, with booster 3,700 W).

1 induction cooking zone 7" (1,800 W, with booster 3,100 W).

1 induction cooking zone 6" (1,400 W, with booster 2,200 W).

Operation

Control knobs with illuminated ring.
Integrated control panel.
Electronic power control in 9 output levels.

Features

Cooking area marking.
Frying sensor function.
Pot detection.
Booster function for each cooking zone.

Safety

Residual heat indication.
Operation indicator.
Safety shut-off.

Planning notes

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of flat bottom cookware is recommended. To insure that the appliance works correctly, the cooktop must be sufficiently ventilated either from the rear or base of the cabinet. Appliance can be snapped into the countertop from above. Appliance weight: approx. 30.8 lbs (14 kg).

Please read additional planning notes on page 117.

Please read the installation details regarding air ducting on page 143.

Rating

Rating: 7,400 W
Minimum fuse protection: 30 A
Electrical: 208 / 220-240 V / 60 Hz
Electrical connection:
Hardwire required, 37" cable length.

