

	INTERNAL BLOWER STANDARD
SINGLE BLOWER (INCLUDED) Min Max. CFM	200 - 700
SINGLE BLOWER (INCLUDED) Min Max. Sones	0.8 - 6
DUAL BLOWER (OPTIONAL) Min Max. CFM	300 - 1,300
DUAL BLOWER (OPTIONAL) Min Max. Sones	1 - 8


INTERNAL BLOWER with ACT™ AIRFLOW CONTROL TECHNOLOGY™* 200 - 590 | 200 - 390 | 200 - 290

*AIRFLOW CONTROL TECHNOLOGY** (ACT**) is an exclusive feature built into specific Zephyr hoods which can limit the maximum blower CFM to meet local code requirements.







shown with optional recirculating kit



TOP





- * 8" round ducting
- ** 10" round ducting
- *** Rectangular ducting

UNDER-CABINET



MODEL		
Stainless Steel	AK7300AS	AK7336AS
Size	30"	36"
BLOWER PERFORMANCE		
Included Blower CFM (Min Max.)	200 - 700	200 - 700
Sones (Min Max.)	0.8 - 6	0.8 - 6
ACT 590 CFM (Min Max.)	200 - 590	200 - 590
ACT 390 CFM (Min Max.)	200 - 390	200 - 390
ACT 290 CFM (Min Max.)	200 - 290	200 - 290
Optional Dual Blower (Min Max.)	NA	300 - 1,300, 1-8 Sones
FEATURES		
Zephyr Connect App Compatible	Yes	Yes
Alexa & Google Home Compatible	Yes	Yes
ACT™ Technology	590, 390, 290, Single Blower Only	590, 390, 290, Single Blower Only
Controls	Proximity Touch	Proximity Touch
Speed Levels	6*	6*
Auto Delay-Off	Yes	Yes
CleanAir Function	Yes	Yes
Lighting	LumiLight LED, 6W x2	LumiLight LED, 6W x2
Tri-Level Lighting	Yes	Yes
Filters	Pro Baffle x2	Pro Baffle x2
Recirculating Option**	Yes	Yes
ADA Compliant	Yes, with Zephyr Connect or	Yes, with Zephyr Connect or
7.27. Compa	Remote	Remote
DUCT SPECIFICATIONS		
Vertical Single Internal Blower	8" Round	8" Round
Horizontal Single Internal Blower	3-1/4" x 10" or 8" Round	3-1/4" x 10" or 8" Round
Vertical Dual Internal Blower	NA	10" Round
Horizontal Dual Internal Blower	NA	NA
AC POWER (Single Blower)	120V, 60Hz at Max. 5A	120V, 60Hz at Max. 5A
AC POWER (Dual Blower)	NA	120V, 60Hz at Max. 9A
OPTIONAL ACCESSORIES		
12" Duct Cover	AK0720	AK0726
24" Duct Cover	AK1720	AK1726
Wireless Remote Control	14000005	14000005
Dual Internal Blower	NA	PBD-1300B
Recirculating Kit	ZRC-7000C	ZRC-7036C
Stainless Steel Telescopic Backsplash		AK1716
Make-Up Air Kit (Single Blower)	MUA008A	MUA008A
Make-Up Air Kit (Dual Blower)	NA	MUA010A
MOUNTING HEIGHT RANGE***	24" - 36"	24" - 36"
WARRANTY	3 years parts, 1 year labor	3 years parts, 1 year labor

^{*}When ACTTM is enabled the maximum speed levels will change. ACT 590 CFM = 5 speeds, ACT 390 CFM = 4 speeds and ACT 290 CFM = 3 speeds.

 $[\]hbox{***Mounting height refers to distance between top of a 36" tall cooking surface and bottom of hood.}$



Zephyr Connect App

Zephyr Connect App allows you to control your range hood from anywhere using your mobile device. It includes real time diagnostics and provides important product information. All you need is a WiFi connection with access to the internet. It seamlessly integrates with your smart devices such as Amazon Alexa or Google Home smart speaker for voice activation. Available to download from Google Play or the App Store.



Airflow Control Technology™ (ACT™)

is an exclusive feature built into specific Zephyr hoods which can limit the maximum blower CFM to meet local code requirements.

PowerWave™ 3-Phase Blower Technology

delivers best-in-class performance with unparalleled quiet operation. It provides more power while minimizing noise and improving efficiency.



^{**}Recirculating kit includes a return-air box which adds an additional 4" to the hood height. Recirculating kit is only compatible with single blower.