QUICK REFERENCE GUIDE > PBE1-24-L Date: 18.08.2025 > 1

# 24" Series 9 Power Burner, LPG

## Series 9



Easily cook for a crowd on the impressive DCS Power Burner. Designed to support different sized pots and woks, it combines powerful heat with precise temperature control from 70,000 to 1,300 BTU.

- Grates are specially designed to provide stability for pots and woks of all sizes
- Combines powerful heat with precise temperature control from 70,000 to 1,300 BTU giving you flexibility for everything from a rapid boil down to a gentle simmer
- Cast brass burners accentuate the high-end aesthetics as well as ensuring the Power
- · Burner will withstand the extremes of mother nature

 Interconnected illuminated dials to match the suite of DCS Series 9 products

## **DIMENSIONS**

Height	10 1/2 "
Width	24 "
Depth	26 7/8 "

## FEATURES & BENEFITS

#### Power With Control

Delivers powerful heat with exceptional control, perfect for large steam pots. Precise temperature control from 70,000 to 1,300 BTU enables a rapid boil down to a gentle simmer.

## Designed To Match

With a matching look across all DCS Series 9 products, you can create a stylish, cohesive design for your Outdoor kitchen. Seamless installation and interconnectivity between products\* allows for unified operation, from ignition to dial illumination.

## Cooking Versatility

The grates are specially designed to provide stability for pots and woks of all sizes, eliminating the need to adjust them. Grates can also be separated into two parts to make cleaning easy.

## **Heavy Duty Build**

Made from durable, cast brass, the burner is designed to withstand high temperatures and all types of weather.

## **SPECIFICATIONS**

#### Features

2 Piece Removable Grates	•
Cast brass burner	•
Ignition system	Surface
Small pot support	•
Stainless steel cover included	•
Wok friendly trivet	•

## Finish

	Material	304 grade
		stainless steel
,	Weather resistant	•

## **Gas Requirements**

1/2" NPT male with 3/8" in flare adapter	•
Gas type	LPG
LP hose with regulator and Type 1 connector	•
Operational pressure	11" W.C.
Supply pressure	12" to 14" W.C.

## **Installation Dimensions**

Cutout depth (proud)	22 3/4 "
Cutout height (proud)	10 1/8 "
Cutout width (proud)	22 1/2 "

### Performance

Inner ring maximum	23000 BTU
--------------------	-----------



QUICK REFERENCE GUIDE > PBE1-24-L Date: 18.08.2025 > 2

Minimum power	1300 BTU	Planning Guide FR - Professional Grills Series 9 Outdoor Kitchen
	47000 BTU 70000 BTU	Planning Guide SP - Professional Grills Series 9 Outdoor Kitchen
Power Requirements  Power and logic interconnectivity  Supply frequency	• 60Hz	Revit-18 Power Burner  Rhino-5 Power Burner  Rhino-5 Power Burner with Insulated Jacket  Rhino-5 Power Burner with Lid  Rhino-5 Power Burner without Lid  Service and Warranty EN FR
Supply voltage	120 V	<ul> <li></li></ul>
<b>Warranty</b> Parts and labor	2 years	<ul> <li>SketchUp-8 Power Burner without Lid</li> <li>User Guide EN</li> <li>User Guide FR</li> </ul>
SKU	71467	A PEACE OF MIND SALE

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © DCS by Fisher & Paykel

## Other product downloads available at dcsappliances.com

2D-DWG Power Burner

Appliances Limited 2020

2D-DXF Power Burner

Installation Guide EN

Installation Guide FR

Planning Guide EN - Professional Grills Series 9 Outdoor Kitchen

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.dcsappliances.com