




**PERFORMANCE DATA SHEET**  
Model: PureSource® 3 Using Replacement Cartridge WF3CB®

APPLICATION GUIDELINES / CONDITIONS OF USE	
Water Supply	Potable Water
Water Temp.	Max. 100°F (38°C), Min. 33°F (0.6°C)
Water Pressure	30 - 100 psi (206.8 - 689.5 kPa)
Service Flow	0.5 gpm maximum (1.9 lpm)
<ul style="list-style-type: none"><li>It is essential that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. See Use &amp; Care Manual for Warranty information.</li><li>While testing was performed under standard laboratory conditions, actual performance may vary.</li><li>The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standard 42, Standard 53 and Standard 401. Spent adsorption media will not be regenerated and used.</li><li>The compounds certified under NSF 401 have been deemed as emerging compounds/incidental contaminants. Emerging compounds/incidental contaminants are those compounds that have been detected in drinking water supplies at trace levels. While occurring at only trace levels, these compounds can affect the public acceptance/perception of drinking water quality.</li></ul>	

**WARNING**

**Read entire manual. Failure to follow all guides and rules could cause personal injury or property damage.** Check with your local public works department for plumbing codes. You must follow their guidelines as you install the Water Filtration system.  
Your Water Filtration system will withstand up to 100 lbs/in² (psi) water pressure.  
**To reduce the risk associated with choking:**  
DO NOT allow children under 3 years of age to have access to small parts during the installation of this product.  
**To reduce the risk associated with the ingestion of contaminants:**  
DO NOT use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after use of the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

REPLACEMENT CARTRIDGE INFORMATION	
Replacement Element: WF3CB®. For estimated cost of replacement elements please call 1-877-4ELECTROLUX (1-877-435-3287) or visit us on the web at Electrolux.com.	
PERFORMANCE DATA	
MODEL: PureSource® 3. Use the replacement cartridge WF3CB®.	
	Certified by IAPMO R&T against NSF/ANSI Standard 42, Standard 53, Standard 401 and Standard CSA B483.1 for the reduction of substances listed below and NSF/ANSI/CAN 372.
SYSTEM SPECIFICATIONS	
Capacity	200 gallons (757 liters)

**CAUTION**

**To reduce the risk associated with property damage due to water leakage or flooding:**

- Read and follow the Use and Care Manual before installation and use of this system.
- Change the disposable filter cartridge at the recommended interval; You MUST replace the disposable filter cartridge every 6 months or sooner.
- Failure to replace the disposable filter cartridge at recommended intervals may lead to reduced filter performance and failure of the filter, causing property damage from water leakage or flooding.
- Installation and use MUST comply with all state and local plumbing codes.
- Protect from freezing, remove filter cartridge when temperatures are expected to drop below 33°F (4.4°C).
- DO NOT install systems in areas where ambient temperatures may go above 110°F (43.3°C).
- DO NOT install on hot water supply lines. The maximum operating water temperature of this filter system is 100°F (37.8°C).

Please refer to the use and care manual for proper maintenance and operation. If this device is not maintained and operated as specified in the use and care manual, there is a risk of exposure to contaminants. For more information, visit [www.frigidaire.com](http://www.frigidaire.com) or the State Water Resources Control Board's Internet Web site at [www.swrcb.ca.gov](http://www.swrcb.ca.gov).  
Patents: This product may be covered by one or more US patents identified at [www.electroluxipnotice.com](http://www.electroluxipnotice.com)

Substance Reduction	NSF/ANSI Specified Challenge Concentration	Maximum Permissible Concentration	NSF Reduction Requirements
Chlorine	2.0 mg/L ± 10%	N/A	≥ 50%
Nominal Particulate Class I	At least 10,000 particles/mL		≥85%
Microplastics			
Atrazine	9 ug/L ± 10%	3 ug/L	N/A
Cysts*	Minimum 50,000 cysts/L	N/A	≥99.95%
			N/A
Lead pH 6.5	150 ug/L ± 10%	5 ug/L	
Lead pH 8.5			
Lindane	2 ug/L ± 10%	0.2 ug/L	
Mercury pH 6.5	6 ug/L ± 10%	2 ug/L	
Mercury pH 8.5			
O-Dichlorobenzene	1800 ug/L ±10%	600 ug/L	
Tetrachloroethylene	15 ug/L ± 10%	5 ug/L	
Monochlorobenzene	2.0 mg/L ± 10%	100 ug/L	
Turbidity	11 ± 1 NTU	0.5 NTU	
Alachlor	0.04 ± 10%	.002 mg/L	
Styrene	2.0 ± 30%	0.1 mg/L	
Toxaphene (Pesticide)	15 ug/L ± 10%	3 ug/L	
2,4-D (Herbicide)	210 ug/L ± 10%	70 ug/L	
Atenolol	200 ng/L ± 20%	30 ng/L	
Ibuprofen (Pharma)	400 ng/L ± 20%	60 ng/L	
Trimethoprim	140 ng/L ± 20%	20 ng/L	

\* Based on the use of Microsphere Cysts



This filter is certified by the Water Quality Association to  
WQA/ASPE/ANSI-803 for sustainability.

Ce filtre est certifié par la Water Quality Association conformément à  
la norme WQA/ASPE/ANSI-803 pour la durabilité.

Este filtro está certificado por la Water Quality Association según  
WQA/ASPE/ANSI-803 por sostenibilidad.