



3-in-1 Connected Portable Room Air Conditioner with Supplemental Heat
14,000 BTU (ASHRAE) / 10,000 BTU (DOE)

Portable Air Conditioner

Available Products: FHPH142AA1

Available Colors: White

Version: 07/25

Product Specifications

AC

Air CFM (Low)	143 CFM
Air CFM (Med)	202 CFM
Air CFM (High)	245 CFM
Air Direction Control	Swing Louver
Air Discharge	Top of Unit
Fan Speeds - Cool	3
Fan Speeds - Fan	3
Fan Speeds - Heat	3
Motor RPM (Low)	1000 RPM
Motor RPM (Med)	1300 RPM
Motor RPM (High)	1500 RPM
Noise Level dBA (Low)	49 dBA
Noise Level dBA (Med)	51 dBA
Noise Level dBA (High)	52 dBA
Quick Glance Light	Yes
Digital Humidity Readout	Yes
Dust Air Filter	Yes
Exhaust Hose	Single Hose
Filter Access Location	Rear
Filter Check Indicator	Yes
Option for Advanced Filtration	Yes
Supplemental Heat	Yes
Window Kit	Yes

Functions

24-Hour On/Off Timer	Yes
Auto Fan	No
Auto Restart	Yes
Clean Air Ionizer	No
Continuous Drain Operation	Yes
Dry Mode	Yes
Energy Saver	No
Low Voltage Start-up	Yes
Sleep Mode	Yes

Dimensions and Volume

Height	31 3/10"
Width	16 3/10"
Depth	18 1/10"

Performance

Cool Area (DOE)	450 sq.
DOE BTU (Cool)	10000 BTU
ASHRAE BTU (Cool)	14000 BTU
BTU (Heat Pump)	12000 BTU
COP (Heat Pump)	10.26
Combined Energy Efficiency Ratio	7.8
Dehumidification - Pints per Hour	4.04
Operating Temperature Low	41 F
Operating Temperature High	95 F

Controls

Child Lock	Yes
Control Type	Electronic
Remote Control	No

Electrical Specifications

Amps (Cool)	10.7 Amps
Amps (Heat Pump)	10.3 Amps
Amps (Start Up)	11.5 Amps
Voltage Rating	115 V
Voltage Rating	115/120v
Watts (Cool)	1206 Watts
Watts (Heat Pump)	1179.7 Watts

General Specifications

Prop 65 Label	Yes
Refrigerant Type	R-32
Warranty - Labor	1 Year
Warranty - Parts	1 Year

Connectivity

Wi-Fi Enabled	Yes
---------------	-----

Safety Certifications and Approvals

cUL Listed	Yes
UL Listed	Yes

3-in-1 Connected Portable Room Air Conditioner with
Supplemental Heat 14,000 BTU (ASHRAE) / 10,000 BTU 5566
(DOE)

Available Products: FHPH142AA1 Available Colors: White

Version: 07/25

Installation

Hose Diameter	6"
Maximum Hose Length	59"
Minimum Hose Length	10 3/5"
Power Cord Length	72"

Performance Certifications and Approvals

ENERGY STAR Certified	No
-----------------------	----

Accessories Sold Separately

PureAir Filter	Yes
----------------	-----