

MVHP264ME4CA

MRV 5 Series Heat Pump
22 Tons

Job Name: _____
 Location: _____
 Date: _____
 Tag: _____

Reference Approval Construction



Specifications

Performance¹

Cooling Capacity	253,000 Btu/h
Heating Capacity	282,000 Btu/h
EER (ducted/non-ducted)	9.80/10.40
IEER (ducted/non-ducted)	20.70/18.80
SCHE (ducted/non-ducted)	N/A
COP 47F (ducted/non-ducted)	3.20/3.20

Technical Details

Compressor Type	DC Inverter 2+1
Compressor RLA	(12.5 + 12.5) + 24
Condenser Fan Qty	2+2
Condenser Fan Type	Propeller
Condenser Fan CFM	10,500 + 10,500
Factory Refrigerant Charge	43.65 + 47.18 lb

Electrical

Voltage (V / Ø / Hz)	460 / 3 / 60
Minimum Circuit Ampacity (MCA)	30A + 22A
Maximum Overcurrent Protection	40A + 30A

Sound Levels²

Sound Power Level, dB(A)	83 + 81
--------------------------	---------

Piping

Total System length	3280 ft.
ODU to furthest IDU	722 ft.
ODU above IDU	295 ft.
ODU below IDU	361 ft.

Features and Benefits

- Optimized, intelligent control with all DC inverter EVI compressor technology achieves high efficiency performance with high reliability
- Wide range of operation from -13°F (-25°C) to 122°F (50°C)
- IEER performance up to 25.0
- COP performance up to 3.6
- Delivers 80% of rated heating capacity at 5°F (-15°C)
- Four-sided heat exchanger reduces chassis footprint
- Hinged electrical box design for ease of access to system components
- Factory standard black fin anti corrosion coating
- Nighttime quiet operation reduces sound levels by 10 dB(A)
- Automatic oil balancing eliminates the need for oil balancing piping
- 10 year limited parts and compressor warranty²

Notes

1. Cooling and heating capacities are based on the following temperatures:
 Cooling Indoor: 80°F DB, 67°F WB
 Cooling Outdoor: 95°F DB
 Heating Indoor: 70°F DB
 Heating Outdoor: 47°F WB, 43°F WB
2. Refer to warranty documentation for complete warranty details.
3. Refer to installation manual for complete installation requirements.



MVHP264ME4CA
 MRV 5 Series Heat Pump
 22 Tons

	Module 1 MVHP144ME4CA	Module 2 MVHP120ME4CA
Technical Details		
Compressor Type	DC Inverter x 2	DC Inverter x 1
Compressor RLA	12.5+12.5 A	16 A
Condenser Fan Qty	2	2
Condenser Fan Type	Propeller	Propeller
Condenser Fan CFM	10,500	10,500
Factory Refrigerant Charge	43.65 lbs.	47.18 lbs.
Electrical		
Voltage (V / Ø / Hz)	460 / 3 / 60	460 / 3 / 60
Minimum Circuit Ampacity (MCA)	30A	22A
Maximum Overcurrent Protection	40A	30A
Sound Levels²		
Sound Power Level, dB(A)	83	81
Dimensions		
Height (in.)	66 1/2	66 1/2
Width (in.)	55 1/2	55 1/2
Depth (in.)	29 1/2	29 1/2
Weight (lb.)	871	750
Piping		
Connections, Liquid/Gas	5/8" x 1 1/8"	5/8" x 1 1/8"

