QUICK REFERENCE GUIDE > BH1-30-N

30" Series 7 Grill, Natural Gas

Series 7



Designed with flexibility in mind, DCS Grills allow you to cook a wide variety of meals and are engineered to deliver the functionality and power demanded by a professional chef. DCS Grills are hand-finished to perfection to complement the quality of the DCS premium outdoor kitchen and built to withstand the demands of the serious cook and the extremes of mother nature. Available in Natural and LP Gas.

DIMENSIONS

Height 24 1/4 "

Width 30 "

Depth 26 5/8 "

FEATURES & BENEFITS

Stainless Steel Burners

The precision ported U-shaped stainless steel burners are rated at a massive 25,000BTU each, offering premium quality and performance. A heat shield directs heat upwards maximizing heating efficiency.

Ceramic Radiant Technology

A layer of ceramic rods provides intense yet even heat. It gives a consistent grilling surface, with controlled heat rather than direct fire.

Direct Burner Ignition

An ergonomic ignition solution, where burners are lit directly from the corresponding knobs.

Temperature Gauge - Zero To Sear

Go from zero to sear with DCS Grills' new built-in temperature gauge. It lets you know exactly how hot the grill is, even when the hood is down.

SPECIFICATIONS

Accessories (sold separately)

Built-in grill cover	ACBI-30
Insulated jacket	BGB30-IJS (optional)
On cart grill cover	ACC-30
Optional cart mount	CAD1-30 / BGB30-CSS

Burners

Number of U-burners

2

Cooking Surface Area

Primary cooking area	553 sq.in.
Total cooking area	748 sq.in.
Warming rack area	195 sq.in.

Features

Full surface searing	•	
Hood temperature gauge	•	
Ignition system	Spark	
Metal dials	•	
Warming rack	•	

Finish

Material	304 grade	
	stainless steel	
Weather resistant	•	

Wedther resistant

Gas Requirements

1/2" NPT male with 3/8" in flare adapter	•
Gas type	NG
Operational pressure	4" W.C.
Supply pressure	6" to 9" W.C.

Installation Dimensions



QUICK REFERENCE GUIDE > BH1-30-N

Cutout depth (proud)	22 3/4 "
Cutout height (proud)	10 1/8 "
Cutout width (proud)	28 1/2 "
Insulated jacket for proud cut-out	Varies - check manual
Performance	
Total Power	50000 BTU
U-burner power	25000 BTU
Power Requirements	
Grill power supply	9V Battery for Ignition

SKU 71639

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © DCS by Fisher & Paykel Appliances Limited 2020

Other product downloads available at dcsappliances.com

- ↓ 2D-DWG
- U 2D-DXF
- Installation Guide Grill on Cart EN
- ↓ Installation Guide EN
 - Installation Guide Grill on Cart FR

- Installation Guide SP
- Planning Guide EN Professional Grills Series 7 Outdoor
 Kitchen
- → Planning Guide FR Professional Grills Series 7 Outdoor Kitchen
- Planning Guide SP Professional Grills Series 7 Outdoor Kitchen
- ↓ Revit
- **↓** Rhino
- ↓ Service and Warranty EN FR
- ↓ SketchUp
- ↓ User Guide EN
- ↓ User Guide FR
- User Guide SP

A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.dcsappliances.com