QUICK REFERENCE GUIDE > BE1-48RCI-L Date: 24.09.2025 > 1

48" Series 9 Grill, Rotisserie and Infrared Sear Burner, LPG

Series 9




Taking your grilling experience to the next level, this Series 9 builtin 48" grill provides the ultimate grilling space for premium outdoor kitchens.

- Infrared sear burner for incredibly fast searing up to 24,000 BTU/hr
- · Cater for a crowd with the secondary cooking surface
- Build into an outdoor BBQ island, or add a cart for a freestanding grill
- U-burners deliver 25,000 BTU/hr total power per burner with precise heat control from 300°F to 1100°F

DIMENSIONS

Height 27 1/4 "
Width 47 15/16 "
Depth 26 7/8 "



FEATURES & BENEFITS

The Perfect Sear

A dedicated searing zone with a dynamic infrared burner allows you to experience a new level of versatility, using a range of cooking methods. The improved dual rail design offers increased control and faster heating, so you can achieve the perfect sear every time.

Charcoal Smoker Tray

Enjoy a smoky barbecue flavour with the ease of instant gas flame ignition. Grill directly on the cooking grate or add wood chips for extra smoke. A W-shaped tray with adjustable vents helps the charcoal last longer.

Heavy-Duty Infrared Rotisserie

An infrared rotisserie burner provides controlled searing heat up to 18,000BTU. Perfect for entertaining, the heavy-duty motor can easily turn a 50lb load. The rotisserie rod is conveniently stored under the drip pan handle.

Intuitive Lighting

Brilliant 12-volt lighting safely illuminates the entire grilling surface when you open the lid. Ideal for night-time cooking, the bezel dial lighting glows white when the grill is on, and orange when the gas and grill are in use.

Easy Lifting Hood

The hood can be opened using one hand for better access and visibility when cooking. You can easily accommodate larger food loads with extra space under the hood.

Extra Cooking Area

Effortlessly cook for a crowd with a secondary cooking space. You can fit a grill pan for slow cooking, roasting and making sauces, or to keep food warm after searing.

Grease Management System™

Our Grease Management System™ reduces flare-ups by channelling grease and oils away from the burner flames during grilling.

SPECIFICATIONS

Accessories (sold separately)

6" accessory storage

ASE6-48

Built-in grill cover

ACBI-48E



QUICK REFERENCE GUIDE > BE1-48RCI-L Date: 24.09.2025 > 2

Griddle plate	BGC-GP	Finish		Supply frequency	60 Hz
Insulated jacket	BGA48-IJS (optional)	Material	304 grade stainless steel	Supply voltage	120 V
Insulated jacket (with storage accessory unit)	BGA54-IJS (optional)	Weather resistant	•		
On cart grill cover	ACC-48E			SKU	71592
Optional cart mount	CAD-48E	Gas Requirements			
		1/2" NPT male	•	The product dimensions and specifications in this	page apply to the specific
Burners		Gas type LPG		product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore	
Number of U-burners	3	LP hose with regulator and Type 1 connec	ctor •	check with Fisher & Paykel's Customer Care Centre	
Sear burner zone	•	Operational pressure	11" W.C.	correctly describes the model currently available. © DCS by Fisher & Pa Appliances Limited 2020	
		Supply pressure	12" to 14" W.C.	Appliances Limited 2020	
Cooking Surface Area		Installation Dimensions		Other product downloads available at dcsa	appliances.com
Primary cooking area	855 sq.in.	installation dimensions			
Secondary cooking area	738 sq.in.	Cutout depth (proud)	22 3/4 "	<u>↓</u> 2D-DWG Grill	
Total cooking area	1593 sq.in.	Cutout height (proud)	10 1/8 "		
		Cutout width (proud)	45 3/4 "		nsulated Jacket
		Insulated jacket for proud cut-out	Varies - check manual		
Features				<u>▼</u>	
Double sided grilling grates	flat and angled position			2D-DXF Grill with Storage Unit2D-DXF Grill with Storage Unit and In	sulated Jacket
Full charcoal burner/smoker	•	Performance			
Full surface searing	•	Rotisserie burner power	18000 BTU	Installation Guide Grill EN	
Grease management system™	•	Sear burner power	24000 BTU	Installation Guide Grill on Cart EN	
Hood temperature gauge	•	Total Power	117000 BTU	✓ Guide d'installation FR✓ Installation Guide Grill on Cart FR	
Ignition system	Hot surface	U-burner power	25000 BTU	✓ Installation Guide Grill on Cart FR✓ Guía de instalación SP	
Metal dials	riot surface	Weight rotisserie can handle	50 lbs		
Rotisserie	•			Planning Guide EN - Professional Grill	s Series 9 Outdoor
Secondary cooking features	2-level racks and			Kitchen	s Sorios a Outdoor
cooling reduces	tray	Dower Dogwingments		Planning Guide FR - Professional Grills Series 9 Outdoor Kitchen	
Wireless temperature sensor compatible	•	Rotisserie power supply	120V 60Hz		



QUICK REFERENCE GUIDE > BE1-48RCI-L Date: 24.09.2025 > 3

- → Planning Guide SP Professional Grills Series 9 Outdoor Kitchen
- ↓ Revit-18 Grill
- ↓ Revit-18 Grill with Storage Unit
- ↓ Rhino-5 Grill
- ↓ Rhino-5 Grill with Storage Unit
- Rhino-5 Grill with Storage Unit and Insulated Jacket
- ↓ Rhino-5 Grill with Insulated Jacket
- ↓ Service and Warranty EN FR
- ↓ Sketchup-8 Grill
- ↓ Sketchup-8 Grill with Storage Unit
- ↓ Sketchup-8 Grill with Storage Unit and Insulated Jacket
- ↓ Sketchup-8 Grill with Storage Unit and Insulated Jacket
- ↓ Guide d'utilisation FR
- ↓ Guía del usuario SP

A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.dcsappliances.com