



Features and Benefits

Design

• Duct Extension Accessory Kit Available for 9' to 11.5' Ceilings

Performance

- 4 Halogen Lights 12 Volt, 20 Watt max., G-4 Base
- 8" round duct at discharge.

Efficiency

- Blower will automatically turn on at high speed if excessive heat is sensed in the control area.
- Absorb odors with charcoal replacement filters.

Convenience

- . Convenient timer built into control from 1-60 minutes.
- Signal on LCD display will illuminate as a reminder to check filters for cleaning.
- . Audible tone when select controls are pressed.

Notes: All height, width and depth dimensions are shown in inches. *Please refer to installation instructions prior to making cutout. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details. Applicable product warranty can be foundin a ccompanying product literature or you may contact your account manager for further details.









Features	
Operating Mode	Convertable: Ducted / Recirculating
Number of speed settings	4-stage
Delay Shut off modes	
Silence level (dBA)	
Required accessories	
Optional accessories	HCIEXT5UC,
	HCIFILTUC, HIREC5UC
Number of lights	4
Type of lamps used	Halogen
Total power of the lamps (W)	
Grease filter material	Washable
	stainless steel
Grease filter type	Multilayer cassette
Clean filter reminders	-
Technical Specification	
UPC code	825225909071
Material	Stainless steel
Watts (W)	610
Current (A)	
Volts (V)	120
Frequency (Hz)	60
Approval certificates	CUL, UL
Power Cord Length	•
Plug type	no plug
Overall appliance dimensions (HxWxD) (in)	29 13/16" - 45 5/16" /
. , , ,	29 13/16" - 50
	5/16 " x 42 1/16" x
Product packaging dimensions (HxWxD) (in)	
Height of the chimney (in)	27 7/16" - 42 7/8"/27
	7/16" - 47 7/8"
Vertical rise height	
Required distance above cooktop/ranges	24"/27"
Net weight (lbs)	101.000
Gross weight (lbs)	113.000
Adjustable feet	
Motor location	Integrated motor
	in hood chimney
Maximum CFM	•
Diameter of air duct (in) top	8
Diameter of air duct (in) back	
Discharge direction	
No-return airflow flap	Yes
•	

Notes: All height, width and depth dimensions are shown in inches. *Please refer to installation instructions prior to making cutout. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details. Applicable product warranty can be foundin a ccompanying product literature or you may contact your account manager for further details.

For more information on our entire line of products, go to boschappliances.com or call 1-800-944-2904.

Copyright ©2020 BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch Gml

Litho Date: 10/2020



