



Product Features

Innovation

Remotely monitor, control, and start through the Home Connect app Flexibility to program custom settings through the Home Connect app Manage Thermador Connected Experience kitchen suite with one network

Access tips and tricks on Home Connect app to master every aspect Opt to receive mobile notifications as a reminder to clean filters

Performance

Select the precise fan speed needed with four different settings

Automatic mode detects temperatures to adjust fan speed automatically

10-min delay shut off ensure lingering odor do not interrupt a course

Delay shut off time can extend or reduce through Home Connect app

Check filter reminder light illuminates after 40 hours of operation

Powerfully Quiet® blowers sold separate and needed to complete install

Remote or inline blowers to reduce noise, integral for top performance

10" round duct discharge

Design

Opt for either wall or island applications to suit your style

Design match to Thermador Professional Series ranges and range tops

Sleek, smooth touch control make cleaning easy with a damp cloth

Beautiful illumination with white multiple level LED lighting

0-100% light slider in Home Connect app allows perfect level of light


Dishwasher-safe stainless steel, commercial-style baffle filters

Built-in remote control panel accessory available, sold separate

Notes: Please refer to installation instructions. Installation instructions are available at www.thermador.com. Specifications are correct at the time of printing. Thermador reserves the right to change product specifications and design at any time, without notice.



Cut-out for insert without liner accessory



38³/₈" – (978 mm)

39^{3/}4" /

measurements in inches (mm)

Product Features

Operating Mode	Ducted
Number of speed settings	4-stage
Delay Shut off modes	10
Optional accessories	REMCPW
Number of lights	2
Type of lamps used	Low consumption
Grease filter material	Washable
	stainless steel

Technical Specification

UPC code	825225935759
Material	Stainless steel
Watts	1356
Fuse protection	15
Volts	120
Frequency	60
Approval certificates	CSA
Power Cord Length	0"
Plug type	fixed connection,
	no plug
Overall appliance dimensions (HxWxD) (in)	12 13/16" / x
	39 3/4" x 22"
Product packaging dimensions (HxWxD)	17.63 x 27.24 x 45.27
Required distance above cooktop/ranges	30"/30"
Net weight	71.000
Gross weight	75.000
Motor location	without motor
Diameter of air duct (in) top	10
No-return airflow flap	Yes

Notes: Please refer to installation instructions. Installation instructions are available at www.thermador.com. Specifications are correct at the time of printing. Thermador reserves the right to change product specifications and design at any time, without notice.