

MVAL015ME2AA

Large 4 Way Cassette Indoor Unit
15,000 Btu/h



Job Name: _____

Location: _____

Date: _____

Tag: _____

Reference

Approval

Construction

Specifications

Performance¹

Cooling Capacity	15,000 Btu/h
Heating Capacity	17,000 Btu/h

Electrical

Voltage (V / Ø / Hz)	208-230 / 1 / 60
Minimum Circuit Ampcity (MCA)	0.63 A
Maximum Overcurrent Protection	15 A
Running Current, Cooling	0.22 A
Running Current, Heating	0.22 A

Fan

Type	Single Turbo
Motor Type	BLDC
Motor Output	36 Watts
Number of Speeds	3 + Auto
Airflow Rate, CFM (H/M/L)	750 / 674 / 588
Airflow Rate, m ³ /h (H/M/L)	1275 / 1145 / 1000

Sound Levels

Sound Power Level, dB(A)	51 / 49 / 45
--------------------------	--------------

Dimensions

Height	8" (204 mm)
Width	33" (840 mm)
Depth	33" (840 mm)
Weight	59.5 lb. (25 kg)

Piping

Refrigerant Type	R410A
Refrigerant - Liquid	1/4" Flare
Refrigerant - Vapor	1/2" Flare
Condensate Drain Outlet	1 1/4" OD

Features and Benefits

- 4-way airflow with stylish panel design
- Six adjustable louver positions
- Built-in condensate lift pump capable of 14" (360mm) lift from drain outlet.
- Low sound levels

Required Accessories

PB-950KB Panel

Optional Accessories and Controls

YR-E16B Programmable Wired Controller

QACT17A Non-Programmable Wired Controller

YR-HBS01 Wireless Remote Controller

YR-HG Wireless Remote Controller

Notes

1. Cooling and heating capacities are based on the following temperatures:
Cooling Indoor: 80°F (26.7°C) DB, 67°F (19.4°C) WB
Cooling Outdoor: 95°F (35°C) DB
Heating Indoor: 70°F (21.1°C) DB
Heating Outdoor: 47°F (8.3°C) WB, 43°F (6.1°C) WB
2. Refer to installation manual for complete installation requirements.
3. Unit ships charged with dry nitrogen.

MRV5
DC INVERTER

MRV-S
SERIES



Dimensions: inch (mm)

No.	Name
1	Gas flare connection
2	Liquid flare connection
3	Drain outlet
4	Return grille
5	Supply louver
6	Drain pipe
7	Power wire inlet
8	PQ comm. inlet

