

MVHP072ME2CA

MRV 5 Series Heat Pump
6 Tons



Job Name: _____
 Location: _____
 Date: _____
 Tag: _____

Reference Approval Construction

Specifications

Performance¹

Cooling Capacity	69,000 Btu/h
Heating Capacity	77,000 Btu/h
EER (ducted/non-ducted)	12.10/13.50
IEER (ducted/non-ducted)	21.00/25.00
SCHE (ducted/non-ducted)	N/A
COP 47F (ducted/non-ducted)	3.60/3.60

Technical Details

Compressor Type	DC Inverter x 1
Compressor RLA	16.7
Condenser Fan Qty	1
Condenser Fan Type	Propeller
Condenser Fan CFM	7,900
Factory Refrigerant Charge	31.97 lbs.

Electrical

Voltage (V / Ø / Hz)	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	29.3A
Maximum Overcurrent Protection	40A

Sound Levels

Sound Power Level, dB(A)	77
--------------------------	----

Dimensions

Height (in.)	66 1/2
Width (in.)	38 5/8
Depth (in.)	29 1/2
Weight (lb.)	597

Piping

Connections, Liquid/Gas	1/2" x 1"
Total System length	3280 ft.
ODU to furthest IDU	722 ft.
ODU above IDU	295 ft.
ODU below IDU	361 ft.

Features and Benefits

- Optimized, intelligent control with all DC inverter EVI compressor technology achieves high efficiency performance with high reliability
- Wide range of operation from -13°F (-25°C) to 122°F (50°C)
- IEER performance up to 25.0
- COP performance up to 3.6
- Delivers 80% of rated heating capacity at 5°F (-15°C)
- Four-sided heat exchanger reduces chassis footprint
- Hinged electrical box design for ease of access to system components
- Factory standard black fin anti corrosion coating
- Nighttime quiet operation reduces sound levels by 10 dB(A)
- Automatic oil balancing eliminates the need for oil balancing piping
- 10 year limited parts and compressor warranty²

Notes

1. Cooling and heating capacities are based on the following temperatures:
 Cooling Indoor: 80°F DB, 67°F WB
 Cooling Outdoor: 95°F DB
 Heating Indoor: 70°F DB
 Heating Outdoor: 47°F WB, 43°F WB
2. Refer to warranty documentation for complete warranty details.
3. Refer to installation manual for complete installation requirements.

MRV5
DC INVERTER


MRV-S
SERIES



Dimensional Drawings

MVHP072ME2CA

Unit: inch (mm)



MVHP096ME2CA

MRV 5 Series Heat Pump
8 Tons



Job Name: _____

Location: _____

Date: _____

Tag: _____

Reference

Approval

Construction

Specifications

Performance¹

Cooling Capacity	92,000 Btu/h
Heating Capacity	103,000 Btu/h
EER (ducted/non-ducted)	12.10/12.00
IEER (ducted/non-ducted)	22.80/23.00
SCHE (ducted/non-ducted)	N/A
COP 47F (ducted/non-ducted)	3.60/3.60

Technical Details

Compressor Type	DC Inverter x 1
Compressor RLA	22.8 A
Condenser Fan Qty	2
Condenser Fan Type	Propeller
Condenser Fan CFM	10,500
Factory Refrigerant Charge	47.18 lbs.

Electrical

Voltage (V / Ø / Hz)	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	34.5A
Maximum Overcurrent Protection	40A

Sound Levels²

Sound Power Level, dB(A)	81
--------------------------	----

Dimensions

Height (in.)	66 1/2
Width (in.)	55 1/2
Depth (in.)	29 1/2
Weight (lb.)	750

Piping

Connections, Liquid/Gas	5/8" x 1 1/8"
Total System length	3280 ft.
ODU to furthest IDU	722 ft.
ODU above IDU	295 ft.
ODU below IDU	361 ft.

Features and Benefits

- Optimized, intelligent control with all DC inverter EVI compressor technology achieves high efficiency performance with high reliability
- Wide range of operation from -13°F (-25°C) to 122°F (50°C)
- IEER performance up to 25.0
- COP performance up to 3.6
- Delivers 80% of rated heating capacity at 5°F (-15°C)
- Four-sided heat exchanger reduces chassis footprint
- Hinged electrical box design for ease of access to system components
- Factory standard black fin anti corrosion coating
- Nighttime quiet operation reduces sound levels by 10 dB(A)
- Automatic oil balancing eliminates the need for oil balancing piping
- 10 year limited parts and compressor warranty²

Notes

1. Cooling and heating capacities are based on the following temperatures:
Cooling Indoor: 80°F DB, 67°F WB
Cooling Outdoor: 95°F DB
Heating Indoor: 70°F DB
Heating Outdoor: 47°F WB, 43°F WB
2. Refer to warranty documentation for complete warranty details.
3. Refer to installation manual for complete installation requirements.

MRV5
DC INVERTER


MRV-S
SERIES



Dimensional Drawings

MVHP096ME2CA

Unit: inch (mm)



No.	Name	Remark
①	Signal line opening (1)	Use rubber grommet for protection
②	Pipe outlet for 2-pipe system	
③	Pipe outlet for 3-pipe system	
④	Power supply opening (2 / 1-2/5)	According to the wire diameter size to choose the appropriate line opening, and using the line sheath in the unit's attachment for protection.
⑤	Hoisting opening (1-3/5)	
⑥	Power supply of signal line opening (1-2/5 / 1-3/4)	
⑦	Refrigerant pipe outlet (2-2/5 / 2-4/5)	
⑧	Drain opening	

MVHP120ME2CA

MRV 5 Series Heat Pump
10 Tons



Job Name: _____

Location: _____

Date: _____

Tag: _____

Reference

Approval

Construction

Specifications

Performance¹

Cooling Capacity	115,000 Btu/h
Heating Capacity	129,000 Btu/h
EER (ducted/non-ducted)	12.10/12.10
IEER (ducted/non-ducted)	23.00/22.00
SCHE (ducted/non-ducted)	N/A
COP 47F (ducted/non-ducted)	3.60/3.60

Technical Details

Compressor Type	DC Inverter x 1
Compressor RLA	24 A
Condenser Fan Qty	2
Condenser Fan Type	Propeller
Condenser Fan CFM	10,500
Factory Refrigerant Charge	47.18 lbs.

Electrical

Voltage (V / Ø / Hz)	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	40.3A
Maximum Overcurrent Protection	50A

Sound Levels²

Sound Power Level, dB(A)	81
--------------------------	----

Dimensions

Height (in.)	66 1/2
Width (in.)	55 1/2
Depth (in.)	29 1/2
Weight (lb.)	750

Piping

Connections, Liquid/Gas	5/8" x 1 1/8"
Total System length	3280 ft.
ODU to furthest IDU	722 ft.
ODU above IDU	295 ft.
ODU below IDU	361 ft.

Features and Benefits

- Optimized, intelligent control with all DC inverter EVI compressor technology achieves high efficiency performance with high reliability
- Wide range of operation from -13°F (-25°C) to 122°F (50°C)
- IEER performance up to 25.0
- COP performance up to 3.6
- Delivers 80% of rated heating capacity at 5°F (-15°C)
- Four-sided heat exchanger reduces chassis footprint
- Hinged electrical box design for ease of access to system components
- Factory standard black fin anti corrosion coating
- Nighttime quiet operation reduces sound levels by 10 dB(A)
- Automatic oil balancing eliminates the need for oil balancing piping
- 10 year limited parts and compressor warranty²

Notes

1. Cooling and heating capacities are based on the following temperatures:
Cooling Indoor: 80°F DB, 67°F WB
Cooling Outdoor: 95°F DB
Heating Indoor: 70°F DB
Heating Outdoor: 47°F WB, 43°F WB
2. Refer to warranty documentation for complete warranty details.
3. Refer to installation manual for complete installation requirements.

MRV5
DC INVERTER


MRV-S
SERIES



Dimensional Drawings

MVHP120ME2CA

Unit: inch (mm)



No.	Name	Remark
①	Signal line opening (1)	Use rubber grommet for protection
②	Pipe outlet for 2-pipe system	
③	Pipe outlet for 3-pipe system	
④	Power supply opening (2 / 1-2/5)	According to the wire diameter size to choose the appropriate line opening, and using the line sheath in the unit's attachment for protection.
⑤	Hoisting opening (1-3/5)	
⑥	Power supply of signal line opening (1-2/5 / 1-3/4)	
⑦	Refrigerant pipe outlet (2-2/5 / 2-4/5)	
⑧	Drain opening	

MVHP144ME2CA

MRV 5 Series Heat Pump
12 Tons



Job Name: _____

Location: _____

Date: _____

Tag: _____

Reference

Approval

Construction

Specifications

Performance¹

Cooling Capacity	138,000 Btu/h
Heating Capacity	154,000 Btu/h
EER (ducted/non-ducted)	11.70/11.60
IEER (ducted/non-ducted)	21.80/22.00
SCHE (ducted/non-ducted)	N/A
COP 47F (ducted/non-ducted)	3.50/3.50

Technical Details

Compressor Type	DC Inverter x 2
Compressor RLA	20.5 + 20.5
Condenser Fan Qty	2
Condenser Fan Type	Propeller
Condenser Fan CFM	10,500
Factory Refrigerant Charge	43.65 lbs.

Electrical

Voltage (V / Ø / Hz)	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	58.9A
Maximum Overcurrent Protection	80A

Sound Levels²

Sound Power Level, dB(A)	83
--------------------------	----

Dimensions

Height (in.)	66 1/2
Width (in.)	55 1/2
Depth (in.)	29 1/2
Weight (lb.)	871

Piping

Connections, Liquid/Gas	5/8" x 1 1/8"
Total System length	3280 ft.
ODU to furthest IDU	722 ft.
ODU above IDU	295 ft.
ODU below IDU	361 ft.

Features and Benefits

- Optimized, intelligent control with all DC inverter EVI compressor technology achieves high efficiency performance with high reliability
- Wide range of operation from -13°F (-25°C) to 122°F (50°C)
- IEER performance up to 25.0
- COP performance up to 3.6
- Delivers 80% of rated heating capacity at 5°F (-15°C)
- Four-sided heat exchanger reduces chassis footprint
- Hinged electrical box design for ease of access to system components
- Factory standard black fin anti corrosion coating
- Nighttime quiet operation reduces sound levels by 10 dB(A)
- Automatic oil balancing eliminates the need for oil balancing piping
- 10 year limited parts and compressor warranty²

Notes

1. Cooling and heating capacities are based on the following temperatures:
Cooling Indoor: 80°F DB, 67°F WB
Cooling Outdoor: 95°F DB
Heating Indoor: 70°F DB
Heating Outdoor: 47°F WB, 43°F WB
2. Refer to warranty documentation for complete warranty details.
3. Refer to installation manual for complete installation requirements.

MRV5
DC INVERTER


MRV-S
SERIES



Dimensional Drawings

MVHP144ME2CA


Unit: inch (mm)



No.	Name	Remark
①	Signal line opening (1)	Use rubber grommet for protection
②	Pipe outlet for 2-pipe system	
③	Pipe outlet for 3-pipe system	
④	Power supply opening (2 / 1-2/5)	According to the wire diameter size to choose the appropriate line opening, and using the line sheath in the unit's attachment for protection.
⑤	Hoisting opening (1-3/5)	
⑥	Power supply of signal line opening (1-2/5 / 1-3/4)	
⑦	Refrigerant pipe outlet (2-2/5 / 2-4/5)	
⑧	Drain opening	

MVHP168ME2CA

MRV 5 Series Heat Pump
14 Tons



Job Name: _____

Location: _____

Date: _____

Tag: _____

Reference

Approval

Construction

Specifications

Performance¹

Cooling Capacity	161,000 Btu/h
Heating Capacity	180,000 Btu/h
EER (ducted/non-ducted)	11.40/11.60
IEER (ducted/non-ducted)	21.60/22.60
SCHE (ducted/non-ducted)	N/A
COP 47F (ducted/non-ducted)	3.40/3.40

Technical Details

Compressor Type	DC Inverter 1+1
Compressor RLA	22.8 + 16.7
Condenser Fan Qty	2+1
Condenser Fan Type	Propeller
Condenser Fan CFM	10,500 + 7,900
Factory Refrigerant Charge	47.18 + 31.97 lb

Electrical

Voltage (V / Ø / Hz)	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	34.5A + 29.3A
Maximum Overcurrent Protection	40A + 40A

Sound Levels²

Sound Power Level, dB(A)	81+77
--------------------------	-------

Piping

Total System length	3280 ft.
ODU to furthest IDU	722 ft.
ODU above IDU	295 ft.
ODU below IDU	361 ft.

Features and Benefits

- Optimized, intelligent control with all DC inverter EVI compressor technology achieves high efficiency performance with high reliability
- Wide range of operation from -13°F (-25°C) to 122°F (50°C)
- IEER performance up to 25.0
- COP performance up to 3.6
- Delivers 80% of rated heating capacity at 5°F (-15°C)
- Four-sided heat exchanger reduces chassis footprint
- Hinged electrical box design for ease of access to system components
- Factory standard black fin anti corrosion coating
- Nighttime quiet operation reduces sound levels by 10 dB(A)
- Automatic oil balancing eliminates the need for oil balancing piping
- 10 year limited parts and compressor warranty²

Notes

1. Cooling and heating capacities are based on the following temperatures:
Cooling Indoor: 80°F DB, 67°F WB
Cooling Outdoor: 95°F DB
Heating Indoor: 70°F DB
Heating Outdoor: 47°F WB, 43°F WB
2. Refer to warranty documentation for complete warranty details.
3. Refer to installation manual for complete installation requirements.

MRV5
DC INVERTER

MRV-S
SERIES



MVHP168ME2CA


 MRV 5 Series Heat Pump
 14 Tons

	Module 1 MVHP096ME2CA	Module 2 MVHP072ME2CA
Technical Details		
Compressor Type	DC Inverter x 1	DC Inverter x 1
Compressor RLA	22.8 A	16.7 A
Condenser Fan Qty	2	1
Condenser Fan Type	Propeller	Propeller
Condenser Fan CFM	10,500	7,900
Factory Refrigerant Charge	47.18 lbs.	31.97 lbs.
Electrical		
Voltage (V / Ø / Hz)	208-230 / 3 / 60	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	34.5 A	29.3 A
Maximum Overcurrent Protection	40 A	40 A
Sound Levels²		
Sound Power Level, dB(A)	81	77
Dimensions		
Height (in.)	66 1/2	66 1/2
Width (in.)	55 1/2	38 5/8
Depth (in.)	29 1/2	29 1/2
Weight (lb.)	750	597
Piping		
Connections, Liquid/Gas	5/8" x 1 1/8"	1/2" x 1"

Dimensional Drawings

MVHP072ME2CA

Unit: inch (mm)




No.	Name	Remark
①	Signal line opening (1)	Use rubber grommet for protection
②	Pipe outlet for 2-pipe system	
③	Pipe outlet for 3-pipe system	
④	Power supply opening (2 / 1-2/5)	According to the wire diameter size to choose the appropriate line opening, and using the line sheath in the unit's attachment for protection.
⑤	Hoisting opening(1-3/5)	
⑥	Power supply of signal line opening(1-2/5 / 1-3/4)	
⑦	Refrigerant pipe outlet (2-2/5 / 2-4/5)	
⑧	Drain opening	

Dimensional Drawings

MVHP096ME2CA

Unit: inch (mm)



No.	Name	Remark
①	Signal line opening (1)	Use rubber grommet for protection
②	Pipe outlet for 2-pipe system	
③	Pipe outlet for 3-pipe system	
④	Power supply opening (2 / 1-2/5)	According to the wire diameter size to choose the appropriate line opening, and using the line sheath in the unit's attachment for protection.
⑤	Hoisting opening (1-3/5)	
⑥	Power supply of signal line opening (1-2/5 / 1-3/4)	
⑦	Refrigerant pipe outlet (2-2/5 / 2-4/5)	
⑧	Drain opening	

MVHP192ME2CA

MRV 5 Series Heat Pump
16 Tons



Job Name: _____
 Location: _____
 Date: _____
 Tag: _____

Reference Approval Construction

Specifications

Performance¹

Cooling Capacity	184,000 Btu/h
Heating Capacity	206,000 Btu/h
EER (ducted/non-ducted)	11.10/11.60
IEER (ducted/non-ducted)	20.60/21.40
SCHE (ducted/non-ducted)	N/A
COP 47F (ducted/non-ducted)	3.30/3.30

Technical Details

Compressor Type	DC Inverter 1+1
Compressor RLA	22.8 + 22.8
Condenser Fan Qty	2+2
Condenser Fan Type	Propeller
Condenser Fan CFM	10,500 + 10,500
Factory Refrigerant Charge	47.18 + 47.18 lb

Electrical

Voltage (V / Ø / Hz)	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	34.5A + 34.5A
Maximum Overcurrent Protection	40A + 40A

Sound Levels²

Sound Power Level, dB(A)	81 + 81
--------------------------	---------

Piping

Total System length	3280 ft.
ODU to furthest IDU	722 ft.
ODU above IDU	295 ft.
ODU below IDU	361 ft.

Features and Benefits

- Optimized, intelligent control with all DC inverter EVI compressor technology achieves high efficiency performance with high reliability
- Wide range of operation from -13°F (-25°C) to 122°F (50°C)
- IEER performance up to 25.0
- COP performance up to 3.6
- Delivers 80% of rated heating capacity at 5°F (-15°C)
- Four-sided heat exchanger reduces chassis footprint
- Hinged electrical box design for ease of access to system components
- Factory standard black fin anti corrosion coating
- Nighttime quiet operation reduces sound levels by 10 dB(A)
- Automatic oil balancing eliminates the need for oil balancing piping
- 10 year limited parts and compressor warranty²

Notes

1. Cooling and heating capacities are based on the following temperatures:
 Cooling Indoor: 80°F DB, 67°F WB
 Cooling Outdoor: 95°F DB
 Heating Indoor: 70°F DB
 Heating Outdoor: 47°F WB, 43°F WB
2. Refer to warranty documentation for complete warranty details.
3. Refer to installation manual for complete installation requirements.

MRV5
DC INVERTER

MRV-S
SERIES



MVHP192ME2CA


 MRV 5 Series Heat Pump
 16 Tons

	Module 1 MVHP096ME2CA	Module 2 MVHP096ME2CA
Technical Details		
Compressor Type	DC Inverter x 1	DC Inverter x 1
Compressor RLA	22.8 A	22.8 A
Condenser Fan Qty	2	2
Condenser Fan Type	Propeller	Propeller
Condenser Fan CFM	10,500	10,500
Factory Refrigerant Charge	47.18 lbs.	47.18 lbs.
Electrical		
Voltage (V / Ø / Hz)	208-230 / 3 / 60	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	34.5 A	34.5 A
Maximum Overcurrent Protection	40 A	40 A
Sound Levels²		
Sound Power Level, dB(A)	81	81
Dimensions		
Height (in.)	66 1/2	66 1/2
Width (in.)	55 1/2	55 1/2
Depth (in.)	29 1/2	29 1/2
Weight (lb.)	750	750
Piping		
Connections, Liquid/Gas	5/8" x 1 1/8"	5/8" x 1 1/8"

Dimensional Drawings

MVHP096ME2CA

Unit: inch (mm)



No.	Name	Remark
①	Signal line opening (1)	Use rubber grommet for protection
②	Pipe outlet for 2-pipe system	
③	Pipe outlet for 3-pipe system	
④	Power supply opening (2 / 1-2/5)	According to the wire diameter size to choose the appropriate line opening, and using the line sheath in the unit's attachment for protection.
⑤	Hoisting opening (1-3/5)	
⑥	Power supply of signal line opening (1-2/5 / 1-3/4)	
⑦	Refrigerant pipe outlet (2-2/5 / 2-4/5)	
⑧	Drain opening	

MVHP216ME2CA

MRV 5 Series Heat Pump
18 Tons



Job Name: _____

Location: _____

Date: _____

Tag: _____

Reference

Approval

Construction

Specifications

Performance¹

Cooling Capacity	207,000 Btu/h
Heating Capacity	232,000 Btu/h
EER (ducted/non-ducted)	10.90/11.50
IEER (ducted/non-ducted)	20.70/20.90
SCHE (ducted/non-ducted)	N/A
COP 47F (ducted/non-ducted)	3.30/3.30

Technical Details

Compressor Type	DC Inverter 1+1
Compressor RLA	24 + 22.8
Condenser Fan Qty	2+2
Condenser Fan Type	Propeller
Condenser Fan CFM	10,500 + 10,500
Factory Refrigerant Charge	47.18 + 47.18 lb

Electrical

Voltage (V / Ø / Hz)	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	40.3A + 34.5A
Maximum Overcurrent Protection	50A + 40A

Sound Levels²

Sound Power Level, dB(A)	81 + 81
--------------------------	---------

Piping

Total System length	3280 ft.
ODU to furthest IDU	722 ft.
ODU above IDU	295 ft.
ODU below IDU	361 ft.

Features and Benefits

- Optimized, intelligent control with all DC inverter EVI compressor technology achieves high efficiency performance with high reliability
- Wide range of operation from -13°F (-25°C) to 122°F (50°C)
- IEER performance up to 25.0
- COP performance up to 3.6
- Delivers 80% of rated heating capacity at 5°F (-15°C)
- Four-sided heat exchanger reduces chassis footprint
- Hinged electrical box design for ease of access to system components
- Factory standard black fin anti corrosion coating
- Nighttime quiet operation reduces sound levels by 10 dB(A)
- Automatic oil balancing eliminates the need for oil balancing piping
- 10 year limited parts and compressor warranty²

Notes

1. Cooling and heating capacities are based on the following temperatures:
Cooling Indoor: 80°F DB, 67°F WB
Cooling Outdoor: 95°F DB
Heating Indoor: 70°F DB
Heating Outdoor: 47°F WB, 43°F WB
2. Refer to warranty documentation for complete warranty details.
3. Refer to installation manual for complete installation requirements.

MRV5
DC INVERTER

MRV-S
SERIES



MVHP216ME2CA


 MRV 5 Series Heat Pump
 18 Tons

	Module 1 MVHP120ME2CA	Module 2 MVHP096ME2CA
Technical Details		
Compressor Type	DC Inverter x 1	DC Inverter x 1
Compressor RLA	24	22.8
Condenser Fan Qty	2	2
Condenser Fan Type	Propeller	Propeller
Condenser Fan CFM	10,500	10,500
Factory Refrigerant Charge	47.18 lbs.	47.18 lbs.
Electrical		
Voltage (V / Ø / Hz)	208-230 / 3 / 60	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	40.3 A	34.5 A
Maximum Overcurrent Protection	50 A	40 A
Sound Levels²		
Sound Power Level, dB(A)	81	81
Dimensions		
Height (in.)	66 1/2	66 1/2
Width (in.)	55 1/2	55 1/2
Depth (in.)	29 1/2	29 1/2
Weight (lb.)	750	750
Piping		
Connections, Liquid/Gas	5/8" x 1 1/8"	5/8" x 1 1/8"

Dimensional Drawings

MVHP120/096ME2CA

Unit: inch (mm)



No.	Name	Remark
①	Signal line opening (1)	Use rubber grommet for protection
②	Pipe outlet for 2-pipe system	
③	Pipe outlet for 3-pipe system	
④	Power supply opening (2 / 1-2/5)	According to the wire diameter size to choose the appropriate line opening, and using the line sheath in the unit's attachment for protection.
⑤	Hoisting opening (1-3/5)	
⑥	Power supply of signal line opening (1-2/5 / 1-3/4)	
⑦	Refrigerant pipe outlet (2-2/5 / 2-4/5)	
⑧	Drain opening	

MVHP240ME2CA

MRV 5 Series Heat Pump
20 Tons



Job Name: _____

Location: _____

Date: _____

Tag: _____

Reference

Approval

Construction

Specifications

Performance¹

Cooling Capacity	230,000 Btu/h
Heating Capacity	258,000 Btu/h
EER (ducted/non-ducted)	10.60/10.60
IEER (ducted/non-ducted)	21.00/19.70
SCHE (ducted/non-ducted)	N/A
COP 47F (ducted/non-ducted)	3.20/3.30

Technical Details

Compressor Type	DC Inverter 1+1
Compressor RLA	24 + 24
Condenser Fan Qty	2+2
Condenser Fan Type	Propeller
Condenser Fan CFM	10,500 + 10,500
Factory Refrigerant Charge	47.18 + 47.18 lb

Electrical

Voltage (V / Ø / Hz)	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	40.3A + 40.3A
Maximum Overcurrent Protection	50A + 50A

Sound Levels²

Sound Power Level, dB(A)	81+81
--------------------------	-------

Piping

Total System length	3280 ft.
ODU to furthest IDU	722 ft.
ODU above IDU	295 ft.
ODU below IDU	361 ft.

Features and Benefits

- Optimized, intelligent control with all DC inverter EVI compressor technology achieves high efficiency performance with high reliability
- Wide range of operation from -13°F (-25°C) to 122°F (50°C)
- IEER performance up to 25.0
- COP performance up to 3.6
- Delivers 80% of rated heating capacity at 5°F (-15°C)
- Four-sided heat exchanger reduces chassis footprint
- Hinged electrical box design for ease of access to system components
- Factory standard black fin anti corrosion coating
- Nighttime quiet operation reduces sound levels by 10 dB(A)
- Automatic oil balancing eliminates the need for oil balancing piping
- 10 year limited parts and compressor warranty²

Notes

1. Cooling and heating capacities are based on the following temperatures:
Cooling Indoor: 80°F DB, 67°F WB
Cooling Outdoor: 95°F DB
Heating Indoor: 70°F DB
Heating Outdoor: 47°F WB, 43°F WB
2. Refer to warranty documentation for complete warranty details.
3. Refer to installation manual for complete installation requirements.

MRV5
DC INVERTER

MRV-S
SERIES



MVHP240ME2CA


 MRV 5 Series Heat Pump
 20 Tons

	Module 1 MVHP120ME2CA	Module 2 MVHP120ME2CA
Technical Details		
Compressor Type	DC Inverter x 1	DC Inverter x 1
Compressor RLA	24 A	24 A
Condenser Fan Qty	2	2
Condenser Fan Type	Propeller	Propeller
Condenser Fan CFM	10,500	10,500
Factory Refrigerant Charge	47.18 lbs.	47.18 lbs.
Electrical		
Voltage (V / Ø / Hz)	208-230 / 3 / 60	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	40.3 A	40.3 A
Maximum Overcurrent Protection	50 A	50 A
Sound Levels²		
Sound Power Level, dB(A)	81	81
Dimensions		
Height (in.)	66 1/2	66 1/2
Width (in.)	55 1/2	55 1/2
Depth (in.)	29 1/2	29 1/2
Weight (lb.)	750	750
Piping		
Connections, Liquid/Gas	5/8" x 1 1/8"	5/8" x 1 1/8"

Dimensional Drawings

MVHP120ME2CA

Unit: inch (mm)



No.	Name	Remark
①	Signal line opening (1)	Use rubber grommet for protection
②	Pipe outlet for 2-pipe system	
③	Pipe outlet for 3-pipe system	
④	Power supply opening (2 / 1-2/5)	According to the wire diameter size to choose the appropriate line opening, and using the line sheath in the unit's attachment for protection.
⑤	Hoisting opening (1-3/5)	
⑥	Power supply of signal line opening (1-2/5 / 1-3/4)	
⑦	Refrigerant pipe outlet (2-2/5 / 2-4/5)	
⑧	Drain opening	

MVHP264ME2CA

MRV 5 Series Heat Pump
22 Tons



Job Name: _____

Location: _____

Date: _____

Tag: _____

Reference

Approval

Construction

Specifications

Performance¹

Cooling Capacity	253,000 Btu/h
Heating Capacity	282,000 Btu/h
EER (ducted/non-ducted)	9.80/10.40
IEER (ducted/non-ducted)	20.70/18.80
SCHE (ducted/non-ducted)	N/A
COP 47F (ducted/non-ducted)	3.20/3.20

Technical Details

Compressor Type	DC Inverter 2+1
Compressor RLA	(20.5 + 20.5) + 24
Condenser Fan Qty	2+2
Condenser Fan Type	Propeller
Condenser Fan CFM	10,500 + 10,500
Factory Refrigerant Charge	43.65 + 47.18 lb

Electrical

Voltage (V / Ø / Hz)	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	58.9A + 40.3A
Maximum Overcurrent Protection	80A + 50A

Sound Levels²

Sound Power Level, dB(A)	83 + 81
--------------------------	---------

Piping

Total System length	3280 ft.
ODU to furthest IDU	722 ft.
ODU above IDU	295 ft.
ODU below IDU	361 ft.

Features and Benefits

- Optimized, intelligent control with all DC inverter EVI compressor technology achieves high efficiency performance with high reliability
- Wide range of operation from -13°F (-25°C) to 122°F (50°C)
- IEER performance up to 25.0
- COP performance up to 3.6
- Delivers 80% of rated heating capacity at 5°F (-15°C)
- Four-sided heat exchanger reduces chassis footprint
- Hinged electrical box design for ease of access to system components
- Factory standard black fin anti corrosion coating
- Nighttime quiet operation reduces sound levels by 10 dB(A)
- Automatic oil balancing eliminates the need for oil balancing piping
- 10 year limited parts and compressor warranty²

Notes

1. Cooling and heating capacities are based on the following temperatures:
Cooling Indoor: 80°F DB, 67°F WB
Cooling Outdoor: 95°F DB
Heating Indoor: 70°F DB
Heating Outdoor: 47°F WB, 43°F WB
2. Refer to warranty documentation for complete warranty details.
3. Refer to installation manual for complete installation requirements.

MRV5
DC INVERTER

MRV-S
SERIES



MVHP264ME2CA


 MRV 5 Series Heat Pump
 22 Tons

	Module 1 MVHP144ME2CA	Module 2 MVHP120ME2CA
Technical Details		
Compressor Type	DC Inverter x 2	DC Inverter x 1
Compressor RLA	20.5+20.5 A	24 A
Condenser Fan Qty	2	2
Condenser Fan Type	Propeller	Propeller
Condenser Fan CFM	10,500	10,500
Factory Refrigerant Charge	43.65 lbs.	47.18 lbs.
Electrical		
Voltage (V / Ø / Hz)	208-230 / 3 / 60	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	58.9A	40.3A
Maximum Overcurrent Protection	80A	50A
Sound Levels²		
Sound Power Level, dB(A)	83	81
Dimensions		
Height (in.)	66 1/2	66 1/2
Width (in.)	55 1/2	55 1/2
Depth (in.)	29 1/2	29 1/2
Weight (lb.)	871	750
Piping		
Connections, Liquid/Gas	5/8" x 1 1/8"	5/8" x 1 1/8"

Dimensional Drawings

MVHP144/120ME2CA

Unit: inch (mm)



No.	Name	Remark
①	Signal line opening (1)	Use rubber grommet for protection
②	Pipe outlet for 2-pipe system	
③	Pipe outlet for 3-pipe system	
④	Power supply opening (2 / 1-2/5)	According to the wire diameter size to choose the appropriate line opening, and using the line sheath in the unit's attachment for protection.
⑤	Hoisting opening (1-3/5)	
⑥	Power supply of signal line opening (1-2/5 / 1-3/4)	
⑦	Refrigerant pipe outlet (2-2/5 / 2-4/5)	
⑧	Drain opening	

MVHP288ME2CA

MRV 5 Series Heat Pump
24 Tons



Job Name: _____

Location: _____

Date: _____

Tag: _____

Reference

Approval

Construction

Specifications

Performance¹

Cooling Capacity	276,000 Btu/h
Heating Capacity	308,000 Btu/h
EER (ducted/non-ducted)	9.80/10.40
IEER (ducted/non-ducted)	19.20/18.20
SCHE (ducted/non-ducted)	N/A
COP 47F (ducted/non-ducted)	3.20/3.20

Technical Details

Compressor Type	DC Inverter 2+1
Compressor RLA	(20.5+20.5A) + (20.5+20.5A)
Condenser Fan Qty	2+2
Condenser Fan Type	Propeller
Condenser Fan CFM	10,500 + 10,500
Factory Refrigerant Charge	43.65 + 43.65 lb

Electrical

Voltage (V / Ø / Hz)	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	58.9A + 58.9A
Maximum Overcurrent Protection	80A + 80A

Sound Levels²

Sound Power Level, dB(A)	83 + 83
--------------------------	---------

Piping

Total System length	3280 ft.
ODU to furthest IDU	722 ft.
ODU above IDU	295 ft.
ODU below IDU	361 ft.

Features and Benefits

- Optimized, intelligent control with all DC inverter EVI compressor technology achieves high efficiency performance with high reliability
- Wide range of operation from -13°F (-25°C) to 122°F (50°C)
- IEER performance up to 25.0
- COP performance up to 3.6
- Delivers 80% of rated heating capacity at 5°F (-15°C)
- Four-sided heat exchanger reduces chassis footprint
- Hinged electrical box design for ease of access to system components
- Factory standard black fin anti corrosion coating
- Nighttime quiet operation reduces sound levels by 10 dB(A)
- Automatic oil balancing eliminates the need for oil balancing piping
- 10 year limited parts and compressor warranty²

Notes

1. Cooling and heating capacities are based on the following temperatures:
Cooling Indoor: 80°F DB, 67°F WB
Cooling Outdoor: 95°F DB
Heating Indoor: 70°F DB
Heating Outdoor: 47°F WB, 43°F WB
2. Refer to warranty documentation for complete warranty details.
3. Refer to installation manual for complete installation requirements.

MRV5
DC INVERTER

MRV-S
SERIES



MVHP288ME2CA


 MRV 5 Series Heat Pump
 24 Tons

	Module 1 MVHP144ME2CA	Module 2 MVHP144ME2CA
Technical Details		
Compressor Type	DC Inverter x 2	DC Inverter x 2
Compressor RLA	20.5+20.5 A	20.5+20.5 A
Condenser Fan Qty	2	2
Condenser Fan Type	Propeller	Propeller
Condenser Fan CFM	10,500	10,500
Factory Refrigerant Charge	43.65 lbs.	43.65 lbs.
Electrical		
Voltage (V / Ø / Hz)	208-230 / 3 / 60	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	58.9A	58.9A
Maximum Overcurrent Protection	80A	80A
Sound Levels²		
Sound Power Level, dB(A)	83	83
Dimensions		
Height (in.)	66 1/2	66 1/2
Width (in.)	55 1/2	55 1/2
Depth (in.)	29 1/2	29 1/2
Weight (lb.)	871	871
Piping		
Connections, Liquid/Gas	5/8" x 1 1/8"	5/8" x 1 1/8"

Dimensional Drawings

MVHP144ME2CA

Unit: inch (mm)



No.	Name	Remark
①	Signal line opening (1)	Use rubber grommet for protection
②	Pipe outlet for 2-pipe system	
③	Pipe outlet for 3-pipe system	
④	Power supply opening (2 / 1-2/5)	According to the wire diameter size to choose the appropriate line opening, and using the line sheath in the unit's attachment for protection.
⑤	Hoisting opening (1-3/5)	
⑥	Power supply of signal line opening (1-2/5 / 1-3/4)	
⑦	Refrigerant pipe outlet (2-2/5 / 2-4/5)	
⑧	Drain opening	

MVHP312ME2CA

MRV 5 Series Heat Pump
26 Tons

Job Name: _____

Location: _____


Date: _____

Tag: _____

Reference

Approval

Construction



Specifications

Performance¹

Cooling Capacity	299,000 Btu/h
Heating Capacity	334,000 Btu/h
EER (ducted/non-ducted)	9.80/10.40
IEER (ducted/non-ducted)	19.00/18.10
SCHE (ducted/non-ducted)	N/A
COP 47F (ducted/non-ducted)	3.20/3.20

Technical Details

Compressor Type	DC Inverter 1+1+1
Compressor RLA	24 + 22.8 + 22.8 A
Condenser Fan Qty	2+2+2
Condenser Fan Type	Propeller
Condenser Fan CFM	10,500 + 10,500 + 10,500
Factory Refrigerant Charge	47.18 + 47.18 + 47.18 lb

Electrical

Voltage (V / Ø / Hz)	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	40.3A + 34.5A + 34.5A
Maximum Overcurrent Protection	50A + 40A + 40A

Sound Levels²

Sound Power Level, dB(A)	81+81+81
--------------------------	----------

Piping

Total System length	3280 ft.
ODU to furthest IDU	722 ft.
ODU above IDU	295 ft.
ODU below IDU	361 ft.

Features and Benefits

- Optimized, intelligent control with all DC inverter EVI compressor technology achieves high efficiency performance with high reliability
- Wide range of operation from -13°F (-25°C) to 122°F (50°C)
- IEER performance up to 25.0
- COP performance up to 3.6
- Delivers 80% of rated heating capacity at 5°F (-15°C)
- Four-sided heat exchanger reduces chassis footprint
- Hinged electrical box design for ease of access to system components
- Factory standard black fin anti corrosion coating
- Nighttime quiet operation reduces sound levels by 10 dB(A)
- Automatic oil balancing eliminates the need for oil balancing piping
- 10 year limited parts and compressor warranty²

Notes

1. Cooling and heating capacities are based on the following temperatures:
Cooling Indoor: 80°F DB, 67°F WB
Cooling Outdoor: 95°F DB
Heating Indoor: 70°F DB
Heating Outdoor: 47°F WB, 43°F WB
2. Refer to warranty documentation for complete warranty details.
3. Refer to installation manual for complete installation requirements.

MRV5
DC INVERTER

MRV-S
SERIES



MVHP312ME2CA


 MRV 5 Series Heat Pump
 26 Tons

	Module 1 MVHP120ME2CA	Module 2 MVHP096ME2CA	Module 3 MVHP096ME2CA
Technical Details			
Compressor Type	DC Inverter x 1	DC Inverter x 1	DC Inverter x 1
Compressor RLA	24 A	22.8 A	22.8 A
Condenser Fan Qty	2	2	2
Condenser Fan Type	Propeller	Propeller	Propeller
Condenser Fan CFM	10,500	10,500	10,500
Factory Refrigerant Charge	47.18 lbs.	47.18 lbs.	47.18 lbs.
Electrical			
Voltage (V / Ø / Hz)	208-230 / 3 / 60	208-230 / 3 / 60	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	40.3 A	29.3 A	29.3 A
Maximum Overcurrent Protection	50 A	40 A	40 A
Sound Levels²			
Sound Power Level, dB(A)	81	81	81
Dimensions			
Height (in.)	66 1/2	66 1/2	66 1/2
Width (in.)	55 1/2	55 1/2	55 1/2
Depth (in.)	29 1/2	29 1/2	29 1/2
Weight (lb.)	750	750	750
Piping			
Connections, Liquid/Gas	5/8" x 1 1/8"	5/8" x 1 1/8"	5/8" x 1 1/8"

Dimensional Drawings

MVHP120/096ME2CA

Unit: inch (mm)



No.	Name	Remark
①	Signal line opening (1)	Use rubber grommet for protection
②	Pipe outlet for 2-pipe system	
③	Pipe outlet for 3-pipe system	
④	Power supply opening (2 / 1-2/5)	According to the wire diameter size to choose the appropriate line opening, and using the line sheath in the unit's attachment for protection.
⑤	Hoisting opening (1-3/5)	
⑥	Power supply of signal line opening (1-2/5 / 1-3/4)	
⑦	Refrigerant pipe outlet (2-2/5 / 2-4/5)	
⑧	Drain opening	

MVHP336ME2CA

MRV 5 Series Heat Pump
28 Tons

Job Name: _____

Location: _____


Date: _____

Tag: _____

Reference

Approval

Construction



Specifications

Performance¹

Cooling Capacity	322,000 Btu/h
Heating Capacity	360,000 Btu/h
EER (ducted/non-ducted)	9.80/10.40
IEER (ducted/non-ducted)	18.60/19.30
SCHE (ducted/non-ducted)	N/A
COP 47F (ducted/non-ducted)	3.20/3.20

Technical Details

Compressor Type	DC Inverter 1+1+1
Compressor RLA	24 + 24 + 22.8 A
Condenser Fan Qty	2+2+2
Condenser Fan Type	Propeller
Condenser Fan CFM	10,500 + 10,500 + 10,500
Factory Refrigerant Charge	47.18 + 47.18 + 47.18 lb

Electrical

Voltage (V / Ø / Hz)	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	40.3A + 40.3A + 34.5A
Maximum Overcurrent Protection	50A + 50A + 40A

Sound Levels²

Sound Power Level, dB(A)	81+81+81
--------------------------	----------

Piping

Total System length	3280 ft.
ODU to furthest IDU	722 ft.
ODU above IDU	295 ft.
ODU below IDU	361 ft.

Features and Benefits

- Optimized, intelligent control with all DC inverter EVI compressor technology achieves high efficiency performance with high reliability
- Wide range of operation from -13°F (-25°C) to 122°F (50°C)
- IEER performance up to 25.0
- COP performance up to 3.6
- Delivers 80% of rated heating capacity at 5°F (-15°C)
- Four-sided heat exchanger reduces chassis footprint
- Hinged electrical box design for ease of access to system components
- Factory standard black fin anti corrosion coating
- Nighttime quiet operation reduces sound levels by 10 dB(A)
- Automatic oil balancing eliminates the need for oil balancing piping
- 10 year limited parts and compressor warranty²

Notes

1. Cooling and heating capacities are based on the following temperatures:
Cooling Indoor: 80°F DB, 67°F WB
Cooling Outdoor: 95°F DB
Heating Indoor: 70°F DB
Heating Outdoor: 47°F WB, 43°F WB
2. Refer to warranty documentation for complete warranty details.
3. Refer to installation manual for complete installation requirements.

MRV5
DC INVERTER

MRV-S
SERIES



MVHP336ME2CA


 MRV 5 Series Heat Pump
 28 Tons

	Module 1 MVHP120ME2CA	Module 2 MVHP120ME2CA	Module 3 MVHP096ME2CA
Technical Details			
Compressor Type	DC Inverter x 1	DC Inverter x 1	DC Inverter x 1
Compressor RLA	24 A	24 A	22.8 A
Condenser Fan Qty	2	2	2
Condenser Fan Type	Propeller	Propeller	Propeller
Condenser Fan CFM	10,500	10,500	10,500
Factory Refrigerant Charge	47.18 lbs.	47.18 lbs.	47.18 lbs.
Electrical			
Voltage (V / Ø / Hz)	208-230 / 3 / 60	208-230 / 3 / 60	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	40.3 A	40.3 A	34.5 A
Maximum Overcurrent Protection	50 A	50 A	40 A
Sound Levels²			
Sound Power Level, dB(A)	81	81	81
Dimensions			
Height (in.)	66 1/2	66 1/2	66 1/2
Width (in.)	55 1/2	55 1/2	55 1/2
Depth (in.)	29 1/2	29 1/2	29 1/2
Weight (lb.)	750	750	750
Piping			
Connections, Liquid/Gas	5/8" x 1 1/8"	5/8" x 1 1/8"	5/8" x 1 1/8"

Dimensional Drawings

MVHP120/096ME2CA

Unit: inch (mm)



No.	Name	Remark
①	Signal line opening (1)	Use rubber grommet for protection
②	Pipe outlet for 2-pipe system	
③	Pipe outlet for 3-pipe system	
④	Power supply opening (2 / 1-2/5)	According to the wire diameter size to choose the appropriate line opening, and using the line sheath in the unit's attachment for protection.
⑤	Hoisting opening (1-3/5)	
⑥	Power supply of signal line opening (1-2/5 / 1-3/4)	
⑦	Refrigerant pipe outlet (2-2/5 / 2-4/5)	
⑧	Drain opening	

MVHP360ME2CA

MRV 5 Series Heat Pump
30 Tons

Job Name: _____

Location: _____


Date: _____

Tag: _____

Reference

Approval

Construction



Specifications

Performance¹

Cooling Capacity	345,000 Btu/h
Heating Capacity	372,000 Btu/h
EER (ducted/non-ducted)	9.80/9.80
IEER (ducted/non-ducted)	18.70/18.70
SCHE (ducted/non-ducted)	N/A
COP 47F (ducted/non-ducted)	3.20/3.20

Technical Details

Compressor Type	DC Inverter 1+1+1
Compressor RLA	24 + 24 + 24 A
Condenser Fan Qty	2+2+2
Condenser Fan Type	Propeller
Condenser Fan CFM	10,500 + 10,500 + 10,500
Factory Refrigerant Charge	47.18 + 47.18 + 47.18 lb

Electrical

Voltage (V / Ø / Hz)	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	40.3A + 40.3A + 40.3A
Maximum Overcurrent Protection	50A + 50A + 50A

Sound Levels²

Sound Power Level, dB(A)	81+81+81
--------------------------	----------

Piping

Total System length	3280 ft.
ODU to furthest IDU	722 ft.
ODU above IDU	295 ft.
ODU below IDU	361 ft.

Features and Benefits

- Optimized, intelligent control with all DC inverter EVI compressor technology achieves high efficiency performance with high reliability
- Wide range of operation from -13°F (-25°C) to 122°F (50°C)
- IEER performance up to 25.0
- COP performance up to 3.6
- Delivers 80% of rated heating capacity at 5°F (-15°C)
- Four-sided heat exchanger reduces chassis footprint
- Hinged electrical box design for ease of access to system components
- Factory standard black fin anti corrosion coating
- Nighttime quiet operation reduces sound levels by 10 dB(A)
- Automatic oil balancing eliminates the need for oil balancing piping
- 10 year limited parts and compressor warranty²

Notes

1. Cooling and heating capacities are based on the following temperatures:
Cooling Indoor: 80°F DB, 67°F WB
Cooling Outdoor: 95°F DB
Heating Indoor: 70°F DB
Heating Outdoor: 47°F WB, 43°F WB
2. Refer to warranty documentation for complete warranty details.
3. Refer to installation manual for complete installation requirements.

MRV5
DC INVERTER

MRV-S
SERIES



MVHP360ME2CA


 MRV 5 Series Heat Pump
 30 Tons

	Module 1 MVHP120ME2CA	Module 2 MVHP120ME2CA	Module 3 MVHP120ME2CA
Technical Details			
Compressor Type	DC Inverter x 1	DC Inverter x 1	DC Inverter x 1
Compressor RLA	24 A	24 A	24 A
Condenser Fan Qty	2	2	2
Condenser Fan Type	Propeller	Propeller	Propeller
Condenser Fan CFM	10,500	10,500	10,500
Factory Refrigerant Charge	47.18 lbs.	47.18 lbs.	47.18 lbs.
Electrical			
Voltage (V / Ø / Hz)	208-230 / 3 / 60	208-230 / 3 / 60	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	40.3 A	40.3 A	40.3 A
Maximum Overcurrent Protection	50 A	50 A	50 A
Sound Levels²			
Sound Power Level, dB(A)	81	81	81
Dimensions			
Height (in.)	66 1/2	66 1/2	66 1/2
Width (in.)	55 1/2	55 1/2	55 1/2
Depth (in.)	29 1/2	29 1/2	29 1/2
Weight (lb.)	750	750	750
Piping			
Connections, Liquid/Gas	5/8" x 1 1/8"	5/8" x 1 1/8"	5/8" x 1 1/8"

Dimensional Drawings

MVHP120ME2CA

Unit: inch (mm)



No.	Name	Remark
①	Signal line opening (1)	Use rubber grommet for protection
②	Pipe outlet for 2-pipe system	
③	Pipe outlet for 3-pipe system	
④	Power supply opening (2 / 1-2/5)	According to the wire diameter size to choose the appropriate line opening, and using the line sheath in the unit's attachment for protection.
⑤	Hoisting opening (1-3/5)	
⑥	Power supply of signal line opening (1-2/5 / 1-3/4)	
⑦	Refrigerant pipe outlet (2-2/5 / 2-4/5)	
⑧	Drain opening	

MVHP384ME2CA

MRV 5 Series Heat Pump
32 Tons

Job Name: _____

Location: _____


Date: _____

Tag: _____

Reference

Approval

Construction



Specifications

Performance¹

Cooling Capacity	364,000 Btu/h
Heating Capacity	384,000 Btu/h
EER (ducted/non-ducted)	9.50/9.50
IEER (ducted/non-ducted)	18.50/18.40
SCHE (ducted/non-ducted)	N/A
COP 47F (ducted/non-ducted)	3.20/3.20

Technical Details

Compressor Type	DC Inverter 1+1+1
Compressor RLA	(20.5+20.5) + 24 + 24 A
Condenser Fan Qty	2+2+2
Condenser Fan Type	Propeller
Condenser Fan CFM	10,500 + 10,500 + 10,500
Factory Refrigerant Charge	43.65 + 47.18 + 47.18 lb

Electrical

Voltage (V / Ø / Hz)	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	58.9A + 40.3A + 40.3A
Maximum Overcurrent Protection	80A + 50A + 50A

Sound Levels²

Sound Power Level, dB(A)	83+81+81
--------------------------	----------

Piping

Total System length	3280 ft.
ODU to furthest IDU	722 ft.
ODU above IDU	295 ft.
ODU below IDU	361 ft.

Features and Benefits

- Optimized, intelligent control with all DC inverter EVI compressor technology achieves high efficiency performance with high reliability
- Wide range of operation from -13°F (-25°C) to 122°F (50°C)
- IEER performance up to 25.0
- COP performance up to 3.6
- Delivers 80% of rated heating capacity at 5°F (-15°C)
- Four-sided heat exchanger reduces chassis footprint
- Hinged electrical box design for ease of access to system components
- Factory standard black fin anti corrosion coating
- Nighttime quiet operation reduces sound levels by 10 dB(A)
- Automatic oil balancing eliminates the need for oil balancing piping
- 10 year limited parts and compressor warranty²

Notes

1. Cooling and heating capacities are based on the following temperatures:
Cooling Indoor: 80°F DB, 67°F WB
Cooling Outdoor: 95°F DB
Heating Indoor: 70°F DB
Heating Outdoor: 47°F WB, 43°F WB
2. Refer to warranty documentation for complete warranty details.
3. Refer to installation manual for complete installation requirements.

MRV5
DC INVERTER

MRV-S
SERIES



MVHP384ME2CA


 MRV 5 Series Heat Pump
 32 Tons

	Module 1 MVHP144ME2CA	Module 2 MVHP120ME2CA	Module 3 MVHP120ME2CA
Technical Details			
Compressor Type	DC Inverter x 2	DC Inverter x 1	DC Inverter x 1
Compressor RLA	20.5+20.5 A	24 A	24 A
Condenser Fan Qty	2	2	2
Condenser Fan Type	Propeller	Propeller	Propeller
Condenser Fan CFM	10,500	10,500	10,500
Factory Refrigerant Charge	43.65 lbs.	47.18 lbs.	47.18 lbs.
Electrical			
Voltage (V / Ø / Hz)	208-230 / 3 / 60	208-230 / 3 / 60	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	58.9 A	40.3 A	40.3 A
Maximum Overcurrent Protection	80 A	50 A	50 A
Sound Levels²			
Sound Power Level, dB(A)	83	81	81
Dimensions			
Height (in.)	66 1/2	66 1/2	66 1/2
Width (in.)	55 1/2	55 1/2	55 1/2
Depth (in.)	29 1/2	29 1/2	29 1/2
Weight (lb.)	871	750	750
Piping			
Connections, Liquid/Gas	5/8" x 1 1/8"	5/8" x 1 1/8"	5/8" x 1 1/8"

Dimensional Drawings

MVHP144/120ME2CA

Unit: inch (mm)



No.	Name	Remark
①	Signal line opening (1)	Use rubber grommet for protection
②	Pipe outlet for 2-pipe system	
③	Pipe outlet for 3-pipe system	
④	Power supply opening (2 / 1-2/5)	According to the wire diameter size to choose the appropriate line opening, and using the line sheath in the unit's attachment for protection.
⑤	Hoisting opening (1-3/5)	
⑥	Power supply of signal line opening (1-2/5 / 1-3/4)	
⑦	Refrigerant pipe outlet (2-2/5 / 2-4/5)	
⑧	Drain opening	

MVHP408ME2CA

MRV 5 Series Heat Pump
34 Tons

Job Name: _____

Location: _____


Date: _____

Tag: _____

Reference

Approval

Construction



Specifications

Performance¹

Cooling Capacity	380,000 Btu/h
Heating Capacity	410,000 Btu/h
EER (ducted/non-ducted)	9.50/9.50
IEER (ducted/non-ducted)	18.10/17.30
SCHE (ducted/non-ducted)	N/A
COP 47F (ducted/non-ducted)	3.20/3.20

Technical Details

Compressor Type	DC Inverter 1+1+1
Compressor RLA	<i>refer to next page</i>
Condenser Fan Qty	2+2+2
Condenser Fan Type	Propeller
Condenser Fan CFM	10,500 + 10,500 + 10,500
Factory Refrigerant Charge	43.65 + 43.65 + 47.18 lb

Electrical

Voltage (V / Ø / Hz)	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	58.9A + 58.9A + 40.3A
Maximum Overcurrent Protection	80A + 80A + 50A

Sound Levels²

Sound Power Level, dB(A)	83+83+81
--------------------------	----------

Piping

Total System length	3280 ft.
ODU to furthest IDU	722 ft.
ODU above IDU	295 ft.
ODU below IDU	361 ft.

Features and Benefits

- Optimized, intelligent control with all DC inverter EVI compressor technology achieves high efficiency performance with high reliability
- Wide range of operation from -13°F (-25°C) to 122°F (50°C)
- IEER performance up to 25.0
- COP performance up to 3.6
- Delivers 80% of rated heating capacity at 5°F (-15°C)
- Four-sided heat exchanger reduces chassis footprint
- Hinged electrical box design for ease of access to system components
- Factory standard black fin anti corrosion coating
- Nighttime quiet operation reduces sound levels by 10 dB(A)
- Automatic oil balancing eliminates the need for oil balancing piping
- 10 year limited parts and compressor warranty²

Notes

1. Cooling and heating capacities are based on the following temperatures:
Cooling Indoor: 80°F DB, 67°F WB
Cooling Outdoor: 95°F DB
Heating Indoor: 70°F DB
Heating Outdoor: 47°F WB, 43°F WB
2. Refer to warranty documentation for complete warranty details.
3. Refer to installation manual for complete installation requirements.

MRV5
DC INVERTER

MRV-S
SERIES



MVHP408ME2CA


 MRV 5 Series Heat Pump
 34 Tons

	Module 1 MVHP144ME2CA	Module 2 MVHP144ME2CA	Module 3 MVHP120ME2CA
Technical Details			
Compressor Type	DC Inverter x 2	DC Inverter x 2	DC Inverter x 1
Compressor RLA	20.5+20.5 A	20.5+20.5 A	24 A
Condenser Fan Qty	2	2	2
Condenser Fan Type	Propeller	Propeller	Propeller
Condenser Fan CFM	10,500	10,500	10,500
Factory Refrigerant Charge	43.65 lbs.	43.65 lbs.	47.18 lbs.
Electrical			
Voltage (V / Ø / Hz)	208-230 / 3 / 60	208-230 / 3 / 60	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	58.9 A	58.9 A	40.3 A
Maximum Overcurrent Protection	80 A	80 A	50 A
Sound Levels²			
Sound Power Level, dB(A)	83	83	81
Dimensions			
Height (in.)	66 1/2	66 1/2	66 1/2
Width (in.)	55 1/2	55 1/2	55 1/2
Depth (in.)	29 1/2	29 1/2	29 1/2
Weight (lb.)	871	871	750
Piping			
Connections, Liquid/Gas	5/8" x 1 1/8"	5/8" x 1 1/8"	5/8" x 1 1/8"

Dimensional Drawings

MVHP144/120ME2CA

Unit: inch (mm)



No.	Name	Remark
①	Signal line opening (1)	Use rubber grommet for protection
②	Pipe outlet for 2-pipe system	
③	Pipe outlet for 3-pipe system	
④	Power supply opening (2 / 1-2/5)	According to the wire diameter size to choose the appropriate line opening, and using the line sheath in the unit's attachment for protection.
⑤	Hoisting opening (1-3/5)	
⑥	Power supply of signal line opening (1-2/5 / 1-3/4)	
⑦	Refrigerant pipe outlet (2-2/5 / 2-4/5)	
⑧	Drain opening	

MVHP432ME2CA

MRV 5 Series Heat Pump
36 Tons

Job Name: _____

Location: _____


Date: _____

Tag: _____

Reference

Approval

Construction



Specifications

Performance¹

Cooling Capacity	400,000 Btu/h
Heating Capacity	420,000 Btu/h
EER (ducted/non-ducted)	9.50/9.50
IEER (ducted/non-ducted)	17.00/17.20
SCHE (ducted/non-ducted)	N/A
COP 47F (ducted/non-ducted)	3.20/3.20

Technical Details

Compressor Type	DC Inverter 1+1+1
Compressor RLA	<i>refer to next page</i>
Condenser Fan Qty	2+2+2
Condenser Fan Type	Propeller
Condenser Fan CFM	10,500 + 10,500 + 10,500
Factory Refrigerant Charge	43.65 + 43.65 + 43.65 lb

Electrical

Voltage (V / Ø / Hz)	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	58.9A + 58.9A + 58.9A
Maximum Overcurrent Protection	80A + 80A + 80A

Sound Levels²

Sound Power Level, dB(A)	83+83+83
--------------------------	----------

Piping

Total System length	3280 ft.
ODU to furthest IDU	722 ft.
ODU above IDU	295 ft.
ODU below IDU	361 ft.

Features and Benefits

- Optimized, intelligent control with all DC inverter EVI compressor technology achieves high efficiency performance with high reliability
- Wide range of operation from -13°F (-25°C) to 122°F (50°C)
- IEER performance up to 25.0
- COP performance up to 3.6
- Delivers 80% of rated heating capacity at 5°F (-15°C)
- Four-sided heat exchanger reduces chassis footprint
- Hinged electrical box design for ease of access to system components
- Factory standard black fin anti corrosion coating
- Nighttime quiet operation reduces sound levels by 10 dB(A)
- Automatic oil balancing eliminates the need for oil balancing piping
- 10 year limited parts and compressor warranty²

Notes

1. Cooling and heating capacities are based on the following temperatures:
Cooling Indoor: 80°F DB, 67°F WB
Cooling Outdoor: 95°F DB
Heating Indoor: 70°F DB
Heating Outdoor: 47°F WB, 43°F WB
2. Refer to warranty documentation for complete warranty details.
3. Refer to installation manual for complete installation requirements.

MRV5
DC INVERTER

MRV-S
SERIES



MVHP432ME2CA


 MRV 5 Series Heat Pump
 36 Tons

	Module 1 MVHP144ME2CA	Module 2 MVHP144ME2CA	Module 3 MVHP144ME2CA
Technical Details			
Compressor Type	DC Inverter x 2	DC Inverter x 2	DC Inverter x 2
Compressor RLA	20.5+20.5 A	20.5+20.5 A	20.5+20.5 A
Condenser Fan Qty	2	2	2
Condenser Fan Type	Propeller	Propeller	Propeller
Condenser Fan CFM	10,500	10,500	10,500
Factory Refrigerant Charge	43.65 lbs.	43.65 lbs.	43.65 lbs.
Electrical			
Voltage (V / Ø / Hz)	208-230 / 3 / 60	208-230 / 3 / 60	208-230 / 3 / 60
Minimum Circuit Ampacity (MCA)	58.9 A	58.9 A	58.9 A
Maximum Overcurrent Protection	80 A	80 A	80 A
Sound Levels²			
Sound Power Level, dB(A)	83	83	83
Dimensions			
Height (in.)	66 1/2	66 1/2	66 1/2
Width (in.)	55 1/2	55 1/2	55 1/2
Depth (in.)	29 1/2	29 1/2	29 1/2
Weight (lb.)	871	871	871
Piping			
Connections, Liquid/Gas	5/8" x 1 1/8"	5/8" x 1 1/8"	5/8" x 1 1/8"

Dimensional Drawings

MVHP144ME2CA

Unit: inch (mm)



No.	Name	Remark
①	Signal line opening (1)	Use rubber grommet for protection
②	Pipe outlet for 2-pipe system	
③	Pipe outlet for 3-pipe system	
④	Power supply opening (2 / 1-2/5)	According to the wire diameter size to choose the appropriate line opening, and using the line sheath in the unit's attachment for protection.
⑤	Hoisting opening (1-3/5)	
⑥	Power supply of signal line opening (1-2/5 / 1-3/4)	
⑦	Refrigerant pipe outlet (2-2/5 / 2-4/5)	
⑧	Drain opening	