XOU15BCSF

15” UNDERCOUNTER BEVERAGE CENTER

LIFESTYLE REFRIGERATION





XOU15BCSF

- Glass Shelves Fully Extend While Loaded
- Tri-Color LED Interior Lighting
- Secure Door Lock
- Shelves Adjust To 15 Different Positions

15” UNDERCOUNTER BEVERAGE CENTER

Store up to 66 (12oz) cans at a frosty 34° to 50° F and still find just what your are looking for. The clear glass shelves fully extend while fully loaded enabling you to see the entire contents at a glance. No more fumbling around or emptying the unit to find what you want.

And because beverages come in all shapes and sizes, the shelves of your XO beverage center can quickly adjust to 15 different positions.


WORLD CLASS SERVICE | COMPREHENSIVE WARRANTIES

OUR LASTING COMMITMENT TO YOU

XOU15BCSF

15” UNDERCOUNTER BEVERAGE CENTER

*Specify R for right hand hinge - or - L for left hand hinge



FEATURES

CAPACITY

Clear Glass Shelves Hold:
(66) 12oz Cans At 34° To 50° F

FEATURES

- Glass shelves fully extend to reveal contents
- Tri-color LED interior lighting
- Secure door lock
- Shelves quickly adjust to 15 different positions
- Holds up to 66 (12oz) cans
- Digital temperature control from 34° to 50° F
- Quiet Operation 39 dBA
- Flush installation design for under counter
- Energy-efficient Low-E Glass
- Removable 3 Bottle Wine Cradle included
- X-Active purifies and circulates air
- ENERGY STAR Certified Residential
- Designed for residential or commercial settings

Note: zero clearance hinges are visible just above and below the door

SPECIFICATIONS

ELECTRICAL	115V 60HZ 1.2 AMP*
DIMENSIONS	H 34 1/8” W 14 15/16” D 23 1/4”
ROUGH IN	H 34 1/4“ min W 15 1/4” D 24”
REFRIGERANT	R600A



Two Different Style Handles Included



3 Bottle Wine Rack Included


ENERGY STAR

XO the next level in luxury appliances

xoappliance.com | 800.966.8300

XO is exclusively distributed by EASTERN MARKETING CORP.
24 Eisenhower Parkway Roseland, NJ 07068


ROUGH-IN DIMENSIONS




All XO undercounter units arrive pre-wired with low profile plugs for easy installation



Need more space - Cut into an adjoining cabinet to reach an outlet there





When installing with The hinge side next to a wall -Leave 1-3/4” clearance gap for cabinet handles.

Door must be able to open a minimum of 90 .

If the door cannot open fully you cannot extend the shelves.