



GE APPLIANCES

VARIABLE REFRIGERANT FLOW HEAT PUMP SYSTEM INDOOR UNIT

MWAD024NE2AA

24K
BTH/h

SUBMITTAL

Job Name:

Purchaser:

Submitted To:

Construction:

Reference:

Approval:


Date:

Submitted By:

Unit:

Drawing #:

LOW ESP SLIM DUCT



Features and Benefits

- Anti-cold air function prevents cold air during startup in heating mode to enhance comfort.
- Constant airflow control maintains stable air volume.
- Optional bottom or rear air return configurations for flexible duct design.
- Enhanced indoor air quality with the Ag+ Silver Ion Filter.
- Integrated condensate drain pump.
- Standard integrated R32 leak detector for enhanced safety and compliance.
- Compact design requires only ~10 inches of vertical space above the ceiling.
- Flexible vertical/horizontal installation orientation.

Specifications

ODU	Marketing Model Name	MWAD024NE2AA
	Nominal Capacity (Btu/h)	24,000
	Dimension: H x W x D (in.)	7-13/16 x 43-5/16 x 17-11/16
	Net Weight (lbs)	44.09
	Sound Level (dBA)	56/54/51/48/46/45/44
	Heating Capacity (Btu/h)	27,000
Electrical	Voltage (V / Ø / Hz)	208-230/1/60
	Minimum Circuit Ampacity (MCA)	0.74
	Maximum Overcurrent Protection	15
	Running Current, Cooling	0.65
	Running Current, Heating	0.65
Fan	Type	Centrifugal
	Motor Type	DC
	Motor Output	30 W
	Number of Speeds	7
	Airflow Rate, CFM (H/M/L)	718/677/612/553/494/470/453
	Airflow Rate, m ³ /h (H/M/L)	1220/1150/1040/940/840/800/770
Refrigerant and Piping	Refrigerant Type/Charge (oz.)	R32 / -
	Liquid Pipe O.D. (in)	1/4
	Gas Pipe O.D. (in)	1/2

For more information visit us:

[GEAppliancesAirAndWater.com](https://www.GEAppliancesAirAndWater.com)

©Copyright 2026 GE Appliances, a Haier Company. GE is a trademark of the General Electric Company. Manufactured under trademark license. GE Appliances has a policy of continuous improvement of its products and reserves the right to change materials and specifications without notice.




GE APPLIANCES
a Haier company

AIR&WATER
SOLUTIONS

Dimensions (unit: in.)

Return Air Opening (Inlet)	40-1/16 *6-15/16 inch
Supply Air Opening (Outlet)	37-6/16*4-11/16 inch



SUBMITTAL REVISION HISTORY

05-08-26: Submittal release.
