

# ARFG15PVDLPW



74.63" x 23.5" x 25" (H x W x D)

PHARMA-VAC Performance Series combination 2-door/2-compressor refrigerator-freezer with factory-installed wireless temperature monitoring device for pharmacy, medical, and life science applications

## Highlights:

Wireless Environmental Temperature Monitoring Device (ETM) to ensure real-time alerts and easy management

Purpose-built design to store medication, pharmaceuticals, and other sensitive materials

Independent dual compressor refrigerator and freezer storage in one slim-fitting footprint to maximize storage capacity without compromising performance

## Product Features:

|                                                            |                                                                                                                                                                                      |
|------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Performance Series Refrigerator-Freezer Combination        | Purpose-built all-refrigerator and all-freezer for vaccine storage in medical, pharmaceutical, and life science applications                                                         |
| Purpose-built design                                       | Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC/VFA guidelines                                                              |
| +/-1°C Variation                                           | The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period |
| Wireless Environmental Temperature Monitoring Device (ETM) | Purpose-built technology to log refrigerator and freezer temperature and ensure the safe storage of biologics, tissues, vaccines, medications, and pharmaceuticals                   |
| Fast setup & secure connectivity                           | ETM setup takes less than 20 minutes and connects to the strongest cellular signal to deliver accurate results                                                                       |
| Real-time alerts                                           | Instant temperature notifications for critical excursions via text, call, or email                                                                                                   |
| NIST calibrated to ISO 17025 regulatory standards          | Logger includes a 2-year certificate of calibration for your records                                                                                                                 |
| Refrigerator window                                        | Triple paned glass on the upper refrigerator section provides a clear view of interior contents                                                                                      |

Space-saving design Allows you to create a full refrigerator-freezer with independent controls in a slim-fitting footprint

SUMMIT APPLIANCE DIVISION, FELIX STORCH, NYS ISO 9001:2015 Certified

770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com

www.summitappliance.com

## ARFG15PVDLPW Specifications:

| Overview                   |                      |
|----------------------------|----------------------|
| Height of Cabinet          | 74.63" (190 cm)      |
| Width                      | 23.5" (60 cm)        |
| Width with Door Open       | 24.0" (61 cm)        |
| Depth                      | 25.0" (64 cm)        |
| Depth with Handle          | 26.5" (67 cm)        |
| Depth with door at 90°     | 46.75" (119 cm)      |
| Capacity                   | 10.74 cu.ft. (304 L) |
| Door                       | White                |
| Cabinet                    | White                |
| US Electrical Safety       | ETL                  |
| Canadian Electrical Safety | ETL-C                |
| Amps                       | 2.0                  |
| Voltage/Frequency          | 115 V AC/60 Hz       |
| Weight                     | 205.0 lbs. (93 kg)   |
| Parts & Labor Warranty     | 2 Years              |
| Compressor Warranty        | 5 Years              |
| UPC                        | 761101159775         |

| Refrigerator-Freezer              |                    |
|-----------------------------------|--------------------|
| Door Swing                        | RHD                |
| Reversible                        | Factory Reversible |
| Adjustable Shelves                | Yes                |
| Interior Light                    | Yes                |
| Refrigerator - Interior Height    | 33.0" (84 cm)      |
| Refrigerator - Interior Width     | 19.5" (50 cm)      |
| Refrigerator - Interior Depth     | 17.5" (44 cm)      |
| Refrigerator - Capacity           | 6.74 cu.ft         |
| Refrigerator - Shelf Type         | Wire               |
| Refrigerator - Shelf Qty          | 3                  |
| Refrigerator - Temperature Range  | 2 to 8°C           |
| Refrigerator - Refrigerant Type   | R600a              |
| Refrigerator - Refrigerant Amount | 1.3 oz.            |
| Freezer - Interior Height         | 17.75" (45 cm)     |
| Freezer - Interior Width          | 15.25" (39 cm)     |
| Freezer - Interior Depth          | 16.5" (42 cm)      |

|                              |              |
|------------------------------|--------------|
| Freezer - Capacity           | 4.0 cu.ft    |
| Freezer - Shelf Type         | Wire         |
| Freezer - Shelf Qty          | 2            |
| Thermostat Type              | Digital      |
| Fan Type                     | Interior     |
| Wheels                       | 4            |
| Freezer - Temperature Range  | -30 to -10°C |
| Freezer - Refrigerant Type   | R290a        |
| Freezer - Refrigerant Amount | 1.2 oz.      |
| Sound Level                  | 44.5 dB      |

