



FF195CSSIF



34" x 19" x 18" (H x W x D)

Commercially approved, ENERGY STAR certified all-refrigerator for built-in or freestanding use with a shallow 18" depth, panel-ready door, and stainless steel cabinet

Highlights:

18" shallow depth makes it ideal for smaller commercial and residential settings

ENERGY STAR certified performance ensures annual savings

Panel-ready door lets you create the perfect look

Product Features:

18" shallow depth	Ideal for home wet bars, island kitchens, and other applications with limited footprint space
ENERGY STAR certified	Rated by the DOE to perform with more efficiency than federal standards require, saving your unit energy and you on higher utility costs
Commercially approved	ETL-S listed to NSF-7 standard and meets UL-471 for use in commercial settings
Panel-ready door	Integrated stainless steel door frame accepts full overlay panels, allowing you to customize the refrigerator door or blend it into your cabinetry design; panel size: 18 7/8" W x 31 9/16" H and at least 3/4" thick; 10 lbs. maximum; customers provide their own handles
Stainless steel wrapped exterior	Cabinet features 304 grade stainless steel construction for added durability and a professional look
Built-in capable	Front-breathing design lets you make the best use of space by installing your appliance under the counter
Automatic defrost	Reduced user maintenance with auto defrost system
Adjustable shelves	Three glass shelves with brake system ensures safe, optimal storage
Door racks	Two chrome racks accommodate a variety of sizes for optimal interior storage



FF195CSSIF Specifications:

Overview	
Nominal Height	34.0" (86 cm)
Height of Cabinet	34.0" (86 cm)
Nominal Width	19.0" (48 cm)
Width	19.0" (48 cm)
Nominal Depth	18.0" (46 cm)
Depth	18.0" (46 cm)
Depth with door at 90°	35.0" (89 cm)
Capacity	3.13 cu.ft. (89 L)
Defrost Type	Automatic
Door	Panel-Ready
Cabinet	Stainless Steel
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Energy Usage/Year	259.0kWh/year
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	80.0 lbs. (36 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101075075
Refrigerator Features	
Door Swing	RHD
Reversible	Factory Reversible
Height Adjustable	Yes
Shelf Type	Glass
Shelf Qty	3
Adjustable Shelves	Yes
Thermostat Type	Dial
Fan Type	Interior
Refrigerant Type	R600a
Refrigerant Amount	0.88oz.
High Side PSI	320.0
Low Side PSI	120.0
Level Legs Qty	2
Interior Light	Yes
Temperature Range	34 to 50°F

Sound Level	33.4 dB
Dimensions	
Interior Height	29.0" (74 cm)
Interior Width	16.0" (41 cm)
Interior Depth	12.75" (32 cm)
Compressor Step Height	7.0" (18 cm)
Compressor Step Width	16.0" (41 cm)
Compressor Step Depth	6.25" (16 cm)

