

# FF7LWBIMED2



33.75" x 23.63" x 23" (H x W x D)

Built-in undercounter auto defrost medical/scientific all-refrigerator with front control panel equipped with a digital thermostat and NIST calibrated thermometer/alarm; includes front lock, hospital grade cord, and internal fan

## Highlights:

Specially designed and featured to meet the CDC, VFC and VFA's guidelines for safe vaccine storage

User-friendly front control panel keeps the thermostat and alarm in reach without having to open the door

Flexible design allows built-in or freestanding use in 24" wide spaces

## Product Features:

|                                     |                                                                                                                                                                                                                                             |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Reliable temperature stability      | Designed and engineered to store vaccines and other sensitive materials under stable temperature conditions                                                                                                                                 |
| Built-in capable                    | Front-breathing system allows the unit to be used built-in                                                                                                                                                                                  |
| Digital thermostat                  | Digital microprocessor for easy and precise temperature management, with all controls externally located for added convenience                                                                                                              |
| High/low temperature alarm          | Audible alarm sounds if the interior temperature rises or falls out of set range                                                                                                                                                            |
| NIST calibrated temperature display | Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button                                                                 |
| Buffered temperature probe          | Thermometer probe is encased in a glycol-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC, VFC and VFA's guidelines |
| Factory installed lock              | Keyed lock conveniently located towards the top of the door for added security (2 keys included)                                                                                                                                            |
| Automatic defrost                   | Reduced maintenance with auto defrost system                                                                                                                                                                                                |
| Internal fan                        | Fan-forced cooling ensures the unit is evenly cooled from top to bottom                                                                                                                                                                     |

## FF7LWBIMED2 Specifications:

| Overview                   |                       |
|----------------------------|-----------------------|
| Nominal Height             | 34.0" (86 cm)         |
| Height of Cabinet          | 33.75" (86 cm)        |
| Nominal Width              | 24.0" (61 cm)         |
| Width                      | 23.63" (60 cm)        |
| Nominal Depth              | 23.0" (58 cm)         |
| Depth                      | 23.0" (58 cm)         |
| Depth with Handle          | 25.0" (64 cm)         |
| Depth with door at 90°     | 45.75" (116 cm)       |
| Capacity                   | 5.5 cu.ft. (156 L)    |
| Defrost Type               | Automatic             |
| Door                       | White                 |
| Cabinet                    | White                 |
| US Electrical Safety       | ETL                   |
| Canadian Electrical Safety | ETL-C                 |
| Amps                       | 1.3                   |
| Voltage/Frequency          | 115 V AC/60 Hz        |
| Weight                     | 100.0 lbs. (45 kg)    |
| Parts & Labor Warranty     | 2 Years               |
| Compressor Warranty        | 5 Years               |
| UPC                        | 761101072456          |
| Refrigerator Features      |                       |
| Door Swing                 | RHD                   |
| Reversible                 | Factory Reversible    |
| Shelf Type                 | Wire                  |
| Shelf Qty                  | 3                     |
| Adjustable Shelves         | Yes                   |
| Thermostat Type            | Digital               |
| Fan Type                   | Interior and Exterior |
| Refrigerant Type           | R600a                 |
| Refrigerant Amount         | 0.64oz.               |
| High Side PSI              | 180.0                 |
| Low Side PSI               | 80.0                  |
| Level Legs Qty             | 4                     |
| Interior Light             | Yes                   |
| Temperature Range          | 2° to 8°C             |
| Dimensions                 |                       |
| Interior Height            | 26.25" (67 cm)        |

|                        |               |
|------------------------|---------------|
| Interior Width         | 21.0" (53 cm) |
| Interior Depth         | 18.0" (46 cm) |
| Compressor Step Height | 5.5" (14 cm)  |
| Compressor Step Width  | 21.0" (53 cm) |
| Compressor Step Depth  | 5.5" (14 cm)  |

