

SBC54OSBIADANK



32.25" x 23.75" x 24.75" (H x W x D)

Built-in undercounter ADA height commercially listed kegerator in stainless steel for outdoor use, tap kit not included

Highlights:

- Weatherproof design holds up in the outdoors
- 32 inch height fits under lower ADA compliant counters
- Commercially listed to NSF-7 standards

Product Features:

ADA compliant height	Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters
Commercially approved	ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings
Built-in capable	Front-breathing design allows fully recessed installation under counters
Tap kit not included	Install your own tapping equipment to create a customized beer cooler
Designed for 1/6 kegs	Interior can store up to two sixtel kegs
304 grade stainless steel exterior	Complete stainless steel construction for easy durability in the outdoors
Professional handle	Curved towel bar style handle in brushed stainless steel
Adjustable thermostat	Interior dial thermostat ensures easy temperature management
Automatic defrost	No-frost operation for minimum user maintenance



SBC54OSBIADANK Specifications:

Overview	
Nominal Height	32.0" (81 cm)
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Nominal Width	24.0" (61 cm)
Width	23.75" (60 cm)
Nominal Depth	25.0" (64 cm)
Depth	24.75" (63 cm)
Depth with Handle	27.25" (69 cm)
Depth with door at 90°	47.0" (119 cm)
Capacity	5.5 cu.ft. (156 L)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.2
Voltage/Frequency	115 V AC/60 Hz
Weight	110.0 lbs. (50 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101069593
Kegerator	
Door Swing	RHD
Reversible	Factory Reversible
Thermostat Type	Dial
Interior Light	Yes
Fan Type	Exterior
Refrigerant	R600a
Refrigerant Amount	0.64 oz.
High Side PSI	180.0
Low Side PSI	80.0
Inter Height	26.25" (67 cm)
Interior Width	21.0" (53 cm)
Interior Depth	17.75" (45 cm)
Compressor Step Height	5.5" (14 cm)
Compressor Step Width	21.0" (53 cm)

Compressor Step Depth	5.5" (14 cm)
Temperature Range	34° to 43°F

