

SBC58BLBIADAIFCMTWIN



32.25" x 23.63" x 22.75" (H x W x D)

Built-in undercounter ADA height commercially listed dual tap combo nitro/cold brew coffee dispenser with panel-ready door and black cabinet

Highlights:

32 inch height fits under lower ADA compliant counters

Commercial grade tap kit includes everything you need to serve both flat iced cold brew and creamy nitro brew drafts

Commercially listed to NSF-7 standards

Product Features:

Dispenses both flat and nitro coffee	Unique combination stout and standard tap system allows you to serve both flat iced cold brew and nitro drafts
ADA compliant height	Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters
Commercially approved	ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings
Built-in capable	Front-breathing design lets you make the best use of space by installing your appliance under the counter
Complete tap kit	Commercial grade tap kit includes a dual tap draft tower with a standard and stout tap, Nitrogen tank, dual gauge regulator, and connections for ball lock Cornelius kegs
Dual tap system	Twin style draft tower allows you to serve from two cornelius style kegs
Panel-ready door	Customize the front by mounting an overlay panel over the door; seamless look can blend into other cabinetry with no exposed frame. Handle not included (panel size: 23 5/16" W x 28 1/4" H and at least 3/4" thick; maximum weight: 10 lbs.)
Adjustable thermostat	Interior dial thermostat ensures easy temperature management

Automatic defrost No frost operation for minimum user maintenance



SBC58BLBIADAIFCMTWIN Specifications:

Overview	
Nominal Height	32.0" (81 cm)
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Nominal Width	24.0" (61 cm)
Width	23.63" (60 cm)
Nominal Depth	23.0" (58 cm)
Depth	22.75" (58 cm)
Depth with door at 90°	45.0" (114 cm)
Capacity	5.5 cu.ft. (156 L)
Defrost Type	Automatic
Door	Panel-Ready
Cabinet	Black
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.2
Voltage/Frequency	115 V AC/60 Hz
Weight	110.0 lbs. (50 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101069678
Kegerator	
Door Swing	RHD
Reversible	Factory Reversible
Tap Kit	Yes
Number of Taps	2
Thermostat Type	Dial
Interior Light	Yes
Fan Type	Exterior
Refrigerant	R600a
Refrigerant Amount	0.64 oz.
High Side PSI	180.0
Low Side PSI	80.0
Inter Height	25.75" (65 cm)
Interior Width	21.0" (53 cm)
Interior Depth	17.75" (45 cm)
Compressor Step Height	6.5" (17 cm)

Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	5.5" (14 cm)
Temperature Range	34° to 43°F

