

# SBC7BRSIFCM2LHD



33.5" x 23.63" x 22.38" (H x W x D)

24" wide commercially approved cold brew/nitro dispenser made in Europe with a twin tap kit to store and serve from two 1/6 kegs; includes panel-ready door, adjustable legs, and caster set for optional mobility

### Highlights:

- Made in Europe
- Dual tap system lets you serve both regular cold brew and nitro coffee
- Panel-ready door lets you customize the unit to best match your style

### Product Features:

|                                           |                                                                                                                                                                                                                                                               |
|-------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 24" Wide Cold Brew/Nitro Coffee Dispenser | Kegerator includes all of the equipment you need to serve cold brew and nitro coffee from two sixtel or Cornelius kegs                                                                                                                                        |
| Made in Europe & the USA                  | Refrigeration unit is constructed in Europe and designed and modified in the USA                                                                                                                                                                              |
| Versatile use                             | Approved for both residential and commercial settings                                                                                                                                                                                                         |
| Commercially listed                       | ETL-S listed to ANSI-NSF Standard 7 for commercial use                                                                                                                                                                                                        |
| Panel-ready door                          | Integrated stainless steel door frame allows you to mount full overlay panels over the door to create a custom look that can blend into cabinetry with no exposed frame (panel size: 23 5/16" W x 28 1/4" H and at least 3/4" thick; maximum weight: 10 lbs.) |
| Dispenses both flat and nitro coffee      | Unique combination stout and standard tap system allows you to serve both flat iced cold brew and nitro drafts                                                                                                                                                |
| Complete cold brew tap kit included       | Commercial grade tap kit includes a dual tap stainless steel draft tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs                                                                                                              |
| Dual tap system                           | Twin draft tower allows you to serve from two 1/6 (sixel) sized kegs                                                                                                                                                                                          |

Slim counter height dimensions for recessed Ideal 24" footprint for an easy fit or freestanding use

## SBC7BRSIFCM2LHD Specifications:

| Overview                   |                     |
|----------------------------|---------------------|
| Nominal Height             | 34.0" (86 cm)       |
| Height of Cabinet          | 33.5" (85 cm)       |
| Nominal Width              | 24.0" (61 cm)       |
| Width                      | 23.63" (60 cm)      |
| Nominal Depth              | 23.0" (58 cm)       |
| Depth                      | 22.38" (57 cm)      |
| Depth with door at 90°     | 44.25" (112 cm)     |
| Capacity                   | 5.3 cu.ft. (150 L)  |
| Defrost Type               | Automatic           |
| Door                       | Integrated Frame    |
| Cabinet                    | Black               |
| US Electrical Safety       | ETL                 |
| Canadian Electrical Safety | ETL-C               |
| Sanitation                 | ETL-S               |
| Energy Usage/Year          | 293.0kWh/year       |
| Amps                       | 0.8                 |
| Voltage/Frequency          | 115 V AC/60 Hz      |
| Weight                     | 100.0 lbs. (45 kg)  |
| Parts & Labor Warranty     | 1 Year              |
| Compressor Warranty        | 5 Years             |
| UPC                        | 761101106311        |
| Kegeerator                 |                     |
| Door Swing                 | LHD                 |
| Reversible                 | Yes                 |
| Height Adjustable          | Yes                 |
| Tap Kit                    | Yes                 |
| Number of Taps             | 2                   |
| Adjustable Shelves         | Yes                 |
| Shelf Type                 | Glass and Scalloped |
| Shelf Qty                  | 4                   |
| Thermostat Type            | Dial                |
| Interior Light             | Yes                 |
| Refrigerant                | R600a               |
| Refrigerant Amount         | 0.64 oz.            |
| Inter Height               | 27.75" (70 cm)      |
| Interior Width             | 21.0" (53 cm)       |
| Interior Depth             | 18.0" (46 cm)       |

|                        |               |
|------------------------|---------------|
| Compressor Step Height | 5.5" (14 cm)  |
| Compressor Step Width  | 21.0" (53 cm) |
| Compressor Step Depth  | 6.0" (15 cm)  |
| Level Legs Qty         | 4             |
| Wheel Qty              | 4             |
| Temperature Range      | 36 to 46°F    |

