

# VT65MLTBC



33.5" x 23.63" x 23.5" (H x W x D)

24 in. wide counter height all-freezer capable of -25° C operation with pure copper handle and front-mounted lock

## Highlights:

Copper towel bar handle kills microbes in a shorter timeframe than other metals for added safety

-25°C operation for safe storage of temperature sensitive materials

Ideal 24" footprint for easy placement in institutional settings

## Product Features:

|                                 |                                                                                                                                        |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Copper handle                   | Naturally antimicrobial, the towel bar handle made from pure copper helps to protect against microbes for added safety and cleanliness |
| -25°C operation                 | Low temperature operation is ideal for certain vaccines, pharmaceuticals, and other temperature sensitive materials                    |
| Factory installed lock          | Keyed lock for a secure interior                                                                                                       |
| Three removable storage drawers | Wire drawers with transparent plastic fronts allow for easy storage organization                                                       |
| Manual defrost                  | Reduced temperature fluctuations with an energy efficient manual defrost system                                                        |
| One-piece interior liner        | Easy clean-up with a seamless liner that won't hold a mess in hidden crevices                                                          |
| Right hand door swing           | For this unit with the door opening from the other side, add option "LHD"                                                              |
| Fully finished white cabinet    | Allows the unit to be used freestanding                                                                                                |
| 100% CFC Free                   | Environmentally friendly design without ozone-damaging chemicals                                                                       |

## VT65MLTBC Specifications:

| Overview                   |                    |
|----------------------------|--------------------|
| Nominal Height             | 34.0" (86 cm)      |
| Height of Cabinet          | 33.5" (85 cm)      |
| Nominal Width              | 24.0" (61 cm)      |
| Width                      | 23.63" (60 cm)     |
| Nominal Depth              | 24.0" (61 cm)      |
| Depth                      | 23.5" (60 cm)      |
| Depth with Handle          | 26.0" (66 cm)      |
| Capacity                   | 3.5 cu.ft. (99 L)  |
| Defrost Type               | Manual             |
| Door                       | White              |
| Cabinet                    | White              |
| US Electrical Safety       | UL                 |
| Canadian Electrical Safety | ULC                |
| Amps                       | 1.3                |
| Voltage/Frequency          | 115 V AC/60 Hz     |
| Weight                     | 105.0 lbs. (48 kg) |
| Parts & Labor Warranty     | 1 Year             |
| Compressor Warranty        | 5 Years            |
| UPC                        | 761101073491       |
| Freezer                    |                    |
| Door Swing                 | RHD                |
| Reversible                 | Factory Reversible |
| Interior Height            | 24.25" (62 cm)     |
| Interior Width             | 17.75" (45 cm)     |
| Interior Depth             | 16.5" (42 cm)      |
| Thermostat Type            | Dial               |
| Refrigerant Type           | R134a              |
| Refrigerant Amount         | 2.76 oz.           |
| Level Legs                 | 2                  |
| Interior Drawers           | Yes                |
| Drawers Qty                | 3                  |
| Temperature Range          | -18°C to -25°C     |

