



GE APPLIANCES

MRV-7 Dual SKU Heat Pump/Heat Recovery VRF



R32 Refrigerant

GWP 675, lower cost.

Flexible Capacity Options Available

Dual Heat Pump/Heat Recovery single-chassis modules available in 6-20T with a 3-module combination up to 36T.

Piping

Flexible long piping length.

Wider Operating Ranges

(-22°F to 115°F) and 5°F 100% heating capacity.

AHU Kit Integration

Supports third-party AHU integration with R32 MRV.

PID Control

±1°F accurate temperature control with dual pressure sensors and dual valves.

Enhanced Corrosion Protection

Standard with anti-corrosion black fin.

Diamond Shield

A multi-layer safety system designed to support safe and reliable operation with A2L refrigerants, incorporating multiple protection features for enhanced system safety and peace of mind.

AVRA

Advanced Variable Refrigerant Adjustment- Optimizes heating and cooling based on outdoor conditions to maximize efficiency and reduce costs.

Quiet Operation

Nighttime quiet operation reduces sound levels by 10dB(A).

Fan

Large 32.3-inch, low-weight fan design.

Brought to you by



GE APPLIANCES
a Haier company

AIR&WATER
SOLUTIONS

MRV-7 Dual SKU Heat Pump/Heat Recovery VRF Specifications



GE APPLIANCES



MWHQ***NC2CA 208-230V VRF

Model	Sound (dBA)	Dimensions (in.)	Approx. Unit Weight (lbs.)	IEER	SCHE	AHRI Rated Capacity BTU/hr
MWHQ072NC2CA	60	66-1/2 x 37 x 32-1/2	598	20.50 / 23.60	23.00 / 32.00	69,000
MWHQ096NC2CA	61	66-1/2 x 37 x 32-1/2	601	21.80 / 23.10	23.60 / 27.20	91,000
MWHQ120NC2CA	61	66-1/2 x 37 x 32-1/2	603	21.60 / 21.80	22.80 / 23.80	115,000



Model	Sound (dBA)	Dimensions (in.)	Approx. Unit Weight (lbs.)	IEER	SCHE	AHRI Rated Capacity BTU/hr
MWHQ144NC2CA	62	66-1/2 x 58-1/3 x 32-1/2	884	20.30 / 21.00	24.30 / 24.20	138,000
MWHQ168NC2CA	72	66-1/2 x 58-1/3 x 32-1/2	884	21.50 / 22.10	27.50 / 28.80	160,000
MWHQ192NC2CA	72	66-1/2 x 58-1/3 x 32-1/2	887	21.10 / 21.10	26.30 / 28.80	184,000
MWHQ216NC2CA	72	66-1/2 x 58-1/3 x 32-1/2	891	20.80 / 21.00	25.50 / 28.60	206,000
MWHQ240NC2CA	72	66-1/2 x 58-1/3 x 32-1/2	891	19.00 / 19.20	25.00 / 28.80	222,000

MWHQ***NC4CA 460V VRF



Model	Sound (dBA)	Dimensions (in.)	Approx. Unit Weight (lbs.)	IEER	SCHE	AHRI Rated Capacity BTU/hr
MWHQ072NC4CA	60	66-1/2 x 37 x 32-1/2	614	20.50 / 23.60	23.00 / 32.00	69,000
MWHQ096NC4CA	61	66-1/2 x 37 x 32-1/2	614	21.80 / 23.10	23.60 / 27.20	91,000
MWHQ120NC4CA	61	66-1/2 x 37 x 32-1/2	618	20.60 / 21.80	22.80 / 23.80	115,000



Model	Sound (dBA)	Dimensions (in.)	Approx. Unit Weight (lbs.)	IEER	SCHE	AHRI Rated Capacity BTU/hr
MWHQ144NC4CA	62	66-1/2 x 58-1/3 x 32-1/2	898	20.30 / 21.00	24.30 / 24.20	138,000
MWHQ168NC4CA	72	66-1/2 x 58-1/3 x 32-1/2	900	21.50 / 22.10	27.50 / 28.80	160,000
MWHQ192NC4CA	72	66-1/2 x 58-1/3 x 32-1/2	900	21.10 / 21.10	26.30 / 28.80	184,000
MWHQ216NC4CA	72	66-1/2 x 58-1/3 x 32-1/2	906	20.80 / 21.00	25.50 / 28.60	206,000
MWHQ240NC4CA	72	66-1/2 x 58-1/3 x 32-1/2	906	19.00 / 19.20	25.00 / 28.80	222,000