



GE APPLIANCES

VRF Medium ESP Duct



R32 Leak Detector

Standard integrated R32 leak detector for enhanced safety and compliance.

Quiet Operation

Low sound levels.

Low Profile Design

Low-profile height design is ideal for limited ceiling space.

IAQ Enhancement

Integrated drain pump and Ag+ silver ion filter for condensate removal and improved indoor air quality.

Airflow Control & Configurable Air Return Options

Maintains stable air volume. Optional air return configurations: Bottom or rear air return for flexible duct design. A single model supports both fresh air and return air functions.

Multiple external static pressure settings available

Static pressure value: 50-150Pa supporting flexible duct design and balanced airflow 0.2" - 0.6".

Brought to you by



GE APPLIANCES
a Haier company

AIR&WATER
SOLUTIONS

VRF Medium ESP Duct Specifications



GE APPLIANCES



MWAM***NE2AA Medium ESP Slim Duct

Model	Sound (dBA)	Dimensions (in.)	Approx. Unit Weight (lbs.)	AHRI Rated Capacity BTU/hr
MWAM005NE2AA	38/36/35/34/33/32/30	9-3/4 x 27-9/16 x 27-9/16	63.0	5,800
MWAM007NE2AA	38/36/35/34/33/32/30	9-3/4 x 27-9/16 x 27-9/16	63.0	7,000
MWAM009NE2AA	38/36/35/34/33/32/30	9-3/4 x 27-9/16 x 27-9/16	63.0	9,000
MWAM012NE2AA	39/37/36/35/34/33/31	9-3/4 x 43-5/16 x 27-9/16	88.2	12,000
MWAM015NE2AA	39/37/36/35/34/33/31	9-3/4 x 43-5/16 x 27-9/16	88.2	15,000
MWAM018NE2AA	44/41/40/39/38/37/35	9-3/4 x 59-1/16 x 27-9/16	116.8	18,000
MWAM024NE2AA	45/42/41/39/38/37/35	9-3/4 x 59-1/16 x 27-9/16	116.8	24,000
MWAM030NE2AA	48/45/44/42/40/38/35	9-3/4 x 59-1/16 x 27-9/16	123.5	30,000
MWAM036NE2AA	48/45/44/42/40/38/35	9-3/4 x 59-1/16 x 27-9/16	123.5	36,000
MWAM042NE2AA	49/46/45/43/41/40/37	9-3/4 x 59-1/16 x 27-9/16	123.5	42,000
MWAM048NE2AA	49/46/45/43/42/40/37	9-3/4 x 59-1/16 x 27-9/16	123.5	48,000
MWAM054NE2AA	49/46/45/43/42/40/37	9-3/4 x 59-1/16 x 27-9/16	123.5	54,000