SCFF532DIM



33.75" x 23.38" x 24" (H x W x D)

Built-in undercounter two-drawer all-freezer with frost-free operation, icemaker, stainless steel construction, and panel-ready drawer fronts

Highlights:

Factory-installed icemaker inside the freezer for a steady supply of ice cubes in the lower drawer

True frost-free operation saves you maintenance by preventing icy buildup

Create the perfect look with panel-ready drawer fronts that can accept custom overlay panels

Product Features:

24" Wide 2-Drawer Freezer	24" wide frost-free freezer for built-in or freestanding use
Factory-installed icemaker	Keep a steady supply of ice cubes on hand in the lower drawer's automatic icemaker
Stainless steel construction	Cabinet, drawers, and kickplate are fully constructed from stainless steel to ensure lasting durability and easy cleanup
Two sliding drawers	Smoothly gliding stainless steel drawers for easy use
Built-in capable	Make the best use of space by installing your appliance under the counter and flush with other cabinets
Panel-ready drawer fronts	Customize your style by installing overlay panels to match or complement adjacent cabinetry (panel size: 23 1/8" W x 14 7/8" W at 3/4" thick)
Frost-free operation	Minimum user maintenance with a fully no-frost operation system
Internal fan	Fan-forced cooling ensures even temperature distribution from top to bottom
Digital thermostat	Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified
770 Garrison Avenue Bronx, NY 10474 USA **TEL** 718-893-3900 **FAX** 844-478-8799 info@summitappliance.com **www.summitappliance.com**

SUMMIT

SCFF532DIM Specifications:

Overview	
Nominal Height	34.0" (86 cm)
Height of Cabinet	33.75" (86 cm)
Nominal Width	24.0" (61 cm)
Width	23.38" (59 cm)
Nominal Depth	24.0" (61 cm)
Depth	24.0" (61 cm)
Depth with Handle	25.75" (65 cm)
Depth with Panel	24.75" (63 cm)
Depth with door at 90°	39.38" (100 cm)
Capacity	4.26 cu.ft. (121 L)
Defrost Type	Frost-Free
Door	Stainless Steel/Panel-Ready
Cabinet	Stainless Steel
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Energy Usage/Year	380.0kWh/year
Amps	1.5
Plug Type	NEMA 5-15P (Right Angle)
Voltage/Frequency	115 V AC/60 Hz
Weight	106.0 lbs. (48 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101145310
Freezer	
Door Swing	Drawer
Thermostat Type	Digital
Interior Light	Yes
Fan Type	Interior and Exterior
Refrigerant Type	R600a
Refrigerant Amount	1.31 oz.
High Side PSI	270.0
Low Side PSI	105.0
Level Legs	2
Interior Drawers	Yes

Drawers Qty	2
Interior Height - Drawer 1	9.25" (23 cm)
Interior Width - Drawer 1	17.25" (44 cm)
Interior Depth - Drawer 1	15.5" (39 cm)
Interior Height - Drawer 2	10.0" (25 cm)
Interior Width - Drawer 2	17.25" (44 cm)
Interior Depth - Drawer 2	15.5" (39 cm)
Compressor Step Height	3.5" (9 cm)
Compressor Step Width	17.25" (44 cm)
Compressor Step Depth	4.0" (10 cm)
Temperature Range	-11°F to 11°F
Star-K Certified	Yes
Sabbath Mode	Yes



SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified
770 Garrison Avenue Bronx, NY 10474 USA **TEL** 718-893-3900 **FAX** 844-478-8799 info@summitappliance.com **www.summitappliance.com**