




PLAN VIEW



FRONT VIEW

PROFILE VIEW



DATA SHEET
Induction Cooktop, 24″, Minimal Style

Model no:
CI244DTB4
(refer page 2 for metric measurements)

Product Dimensions	**in**
Ⓐ Overall height of cooktop	3 7 /8″
Ⓑ Overall width of cooktop	23 9/16″
Ⓒ Overall depth of cooktop	20 7/8″
Ⓓ Height of cooktop glass	1/4″
Ⓔ Height of chassis including conduit junction	3 5/8″
Ⓕ Width of chassis	21 3/4″
Ⓖ Depth of chassis	18 7/8″
Ⓗ Distance from side edges of cooktop to chassis	15/16″
Ⓘ Distance from front edge of cooktop to chassis	1/2″
Ⓙ Distance from back edge of cooktop to chassis	1 1/2″
Ⓚ Distance from front of cooktop to center of conduit junction	6 5/8″
Ⓛ Distance from right of cooktop to center of conduit junction	3 7/8″

Product Clearances	**in**
Minimum clearance from side edges of cutout to nearest combustible surface	1 3/16″
Minimum clearance from rear edge of cutout to nearest combustible surface	1 9/16″
Minimum clearance from counter top to top of any appliances, companion product or obstruction below cooktop*	3 3/4″
Minimum clearance from glass surface to: - overhead cabinet centered above the cooktop (unprotected) - overhead cabinet centered above the cooktop (protected) - rangehood	 30″ 24″ 25 5/8″
Minimum clearance from glass surface to overhead cabinet not directly above cooktop	17 3/4″
Minimum ventilation gap between bottom of counter and top of cabinetry fronts (not shown)	3/16″

*Clearance for proud installation of the cooktop. For flush install the height of the cooktop glass needs to be added to the clearance.

NOTE: The oven installed below the cooktop MUST have a cooling fan. It is important that the induction cooktop receives adequate air supply. For ventilation requirements please refer to the installation manual.


Cutout Dimensions	**in**
Overall width of cutout**	22 1/16″
Overall depth of cutout***	19 5/16″

**NOTE: Cutout position is centered to the cooktop width
***NOTE: Cutout is offset 3/8″ fron the front of the cooktop


INDICATES CUTOUT ----------
INDICATES CABINETRY / PRODUCT DATUM ----------
INDICATES CABINETRY CLEARANCES ----------

DATE: **08.12.2021**

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16″). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com



PLAN VIEW



FRONT VIEW

PROFILE VIEW



DATA SHEET
Induction Cooktop, 24", Minimal Style

Model no:
CI244DTB4
(refer page 1 for imperial measurements)

Product Dimensions	**mm**
Ⓐ Overall height of cooktop	98
Ⓑ Overall width of cooktop	599
Ⓒ Overall depth of cooktop	530
Ⓓ Height of cooktop glass	6
Ⓔ Height of chassis including conduit junction	92
Ⓕ Width of chassis	552
Ⓖ Depth of chassis	480
Ⓗ Distance from side edges of cooktop to chassis	24
Ⓘ Distance from front edge of cooktop to chassis	13
Ⓙ Distance from back edge of cooktop to chassis	38
Ⓚ Distance from front of cooktop to center of conduit junction	168
Ⓛ Distance from right of cooktop to center of conduit junction	98

Product Clearances	**mm**
Minimum clearance from side edges of cutout to nearest combustible surface	30
Minimum clearance from rear edge of cutout to nearest combustible surface	39
Minimum clearance from counter top to top of any appliances, companion product or obstruction below cooktop*	95
Minimum clearance from glass surface to: - overhead cabinet centered above the cooktop (unprotected) - overhead cabinet centered above the cooktop (protected) - rangehood	 762 610 650
Minimum clearance from glass surface to overhead cabinet not directly above cooktop	450
Minimum ventilation gap between bottom of counter and top of cabinetry fronts (not shown)	4

*Clearance for proud installation of the cooktop. For flush install the height of the cooktop glass needs to be added to the clearance.

NOTE: The oven installed below the cooktop MUST have a cooling fan. It is important that the induction cooktop receives adequate air supply. For ventilation requirements please refer to the installation manual.

Cutout Dimensions	**mm**
Overall width of cutout	560
Overall depth of cutout	490

**NOTE: Cutout position is centered to the cooktop width
***NOTE: Cutout is offset 9mm fron the front of the cooktop

INDICATES CUTOUT ----------
INDICATES CABINETRY / PRODUCT DATUM ----------
INDICATES CABINETRY CLEARANCES ----------

DATE: **08.12.2021**

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (1/16"). Please read the installation manual for detailed information on installing the product. For full installation instructions & specifications visit fisherpaykel.com