


SPECIFYING PROCEDURE FOR OPTIONAL RIGID/SWIVEL SPOUTS:

1. Select **BASE PRODUCT** with **Standard Gooseneck Spout**, and with spout outlet and handles required.
2. Select **Optional Rigid/Swivel Spout R** OR **LS-R** ("ADD-ON" Suffix Number)
3. Attach "ADD-ON" Suffix Number Spout selected to Base Product as a dash Suffix. (-R) or (-LS-R)


Note: Refer to BASE PRODUCT specification sheet for suffix availability.

- EG: 1. (1) **Base Product selected:** 23C644
 (2) **Optional Spout selected:** LS-R7
 (3) **End Product Number to Specify:** 23C644-LS-R7
- EG: 2. (1) **Base Product selected:** 27T3924
 (2) **Optional Spout selected:** R7
 (3) **End Product Number to Specify:** 27T3924-R7


GROUP NO. 1 Regular Gooseneck



GROUP NO. 2 Smooth End- Flow Control in Base of Gooseneck Spout (Available on #7 outlets ONLY)



GROUP NO. 5 Double Joint



Require a female aerator

SPOUT GROUP NUMBER	Rigid Swivel "ADD-ON" SUFFIX NUMBER	LIMITED SWING "ADD-ON" SUFFIX NUMBER	RIGID/SWIVEL SPOUT DESCRIPTION	"A"		"C"		"L"	
				mm	in.	mm	in.	mm	in.
1	R2	LS-R2	Gooseneck Spout	114	4.5	104	4.1	170	6.7
	R3	LS-R3	Gooseneck Spout	152	6	124	4.9	56	2.2
	R4	LS-R4	Gooseneck Spout	152	6	124	4.9	146	5.8
	R5	LS-R5	Gooseneck Spout	152	6	124	4.9	188	7.4
	R6	LS-R6	Gooseneck Spout	152	6	124	4.9	229	9
	R7	LS-R7	Gooseneck Spout	229	9	163	6.4	170	6.7
	R35	LS-R35	Gooseneck Spout	152	6	124	4.9	94	3.7
2	R2	LS-R2	GN Spout w/Flow Cont.	114	4.5	97	3.8	178	7
	R3	LS-R3	GN Spout w/Flow Cont.	152	6	117	4.6	64	2.5
	R4	LS-R4	GN Spout w/Flow Cont.	152	6	117	4.6	152	6
	R5	LS-R5	GN Spout w/Flow Cont.	152	6	117	4.6	196	7.7
	R6	LS-R6	GN Spout w/Flow Cont.	152	6	117	4.6	236	9.3
	R7	LS-R7	GN Spout w/Flow Cont.	229	9	155	6.1	178	7
5	R35	LS-R35	GN Spout w/Flow Cont.	152	6	117	4.6	102	4
	R17	—	Double Joint Spout	359	14.1	38	1.5	218	8.6

ALL gooseneck spouts are made from .09 heavy wall seamless brass pipe.

Note: Measurements may vary $\pm 6\text{mm}$ (0.25")

Refer to www.specselect.com for individual models.