


Rigid/Swivel Optional Spouts


TECK®
COMMERCIAL




GROUP NO. 1
Regular
Gooseneck



GROUP NO. 2
Smooth End-Flow
Control
in Base of
Gooseneck Spout
(Available on
#7 or #8 outlets
ONLY)



GROUP NO. 3
Double Joint



SPOUT GROUP NUMBER	RIGID SWIVEL SUFFIX NUMBER	OPTIONAL SPOUTS (SEPARATE ORDER)	LIMITED SWING SUFFIX NUMBER	OPTIONAL SPOUTS (SEPARATE ORDER)	SPOUT DESCRIPTION	"A"		"C"		"L"	
						mm	in.	mm	in.	mm	in.
1	R2	063087A	—	—	Gooseneck Spout	114	4.5	104	4.1	170	6.7
	R4	063088A	LS-R4	063065A	Gooseneck Spout	152	6	124	4.9	146	5.8
	R5	063089A	—	—	Gooseneck Spout	152	6	124	4.9	188	7.4
	R6	063090A	—	—	Gooseneck Spout	152	6	124	4.9	229	9
	R7	063091A	—	—	Gooseneck Spout	229	9	163	6.4	170	6.7
2	R2	060878A	—	—	GN Spout w/Flow Control	114	4.5	97	3.8	178	7
	R4	060872A	—	—	GN Spout w/Flow Control	152	6	117	4.6	152	6
	R7	060875A	—	—	GN Spout w/Flow Control	229	9	155	6.1	178	7
3	R17	063015A 060269A	—	—	Double Joint Spout	381	15.0	48	1.9	218	8.6

ALL gooseneck spouts are made from .09 heavy wall seamless brass pipe.
Swing spout portion of R17 is brass tubular wall spout.

Note: Measurements may vary $\pm 6\text{mm}$ (0.25")

Refer to www.specselect.com for individual models.