

PFD 104 SCVi XXL [MAR]

Fully integrated Full-sized dishwasher with 3D MultiFlex Tray with baskets approved by Lloyd's Register.



- Wash performance: 14 place settings in just 24 min*
- 13% less energy consumption
- Door closes on its own – AutoClose
- Innovative design and maximum convenience – 3D MultiFlex Tray

* Depending on site conditions (temperature of incoming water / power connection) values given may vary.

EAN: 4002516424192 / Material number: 11750900 /
Old Material Number: 61010415MAR

Construction type and design	
Model	Fully integrated dishwasher
XXL dishwashers	•
Range	ProfiLine
Wash system	Fresh water front loader
Number of levels	2
Front	Without front
Side walls	Galvanised
Control panel color	Obsidian Black
Application	
Suitable for offshore and marine services	•
Performance data	
Tested virucidal efficacy	•
Certified hygiene	•
Shortest program duration in min.	24
Maximum final rinse temperature in °F (°C)	167 (75)
Cleaning performance, place settings/cycle	14
Service life in wash cycles	12500
Control	
Control system	Electronic controls
Program selection	Program selectors
Max. delay start in h	24
Countdown indicator	•
Dishwashing programs [number]	8
Program sequence indicator	•
Choice of display language	•
Check filter indicator	•
Standard electrical connection	
Electrical connection	2N AC 120/208-240V, 60HZ
Heater rating in kW	3.50-3.80
Total connected load in kW	3.70-4.00
Fuse rating in A	30
Length of power cord in ft (m)	5 (1.70)
Possible voltage variant 1	
Electrical connection	AC 120V 60HZ
Heater rating in kW	1.30
Total connected load in kW	1.40
Fuse rating in A	15
Water connection/drainage	
Cold or hot water [number]	1
Required flow pressure in bar	1.00-10.00
Drain hose [DN]	22
Maximum delivery head for drain pump in inches (cm)	39 3/8 (100)
Integrated water softener	•
Maximum water hardness in gpg (mmol/l)	38.02 (6.50)
Water protection system	Waterproof system
Length of water drain hose in inches (cm)	59 1/8 (150)

PFD 104 SCVi XXL [MAR]

Fully integrated Full-sized dishwasher with 3D MultiFlex Tray
with baskets approved by Lloyd's Register.



EAN: 4002516424192 / Material number: 11750900 /
Old Material Number: 61010415MAR

Dimensions and weight

External dimensions, net height in inches	33 5/16 (845)
External dimensions, net width in inches	23 9/16 (598)
External dimensions, net depth in inches	21 11/16 (550)
External dimensions, gross height in inches	38 1/4 (970)
External dimensions, gross width in inches	26 7/16 (670)
External dimensions, gross depth in inches	27 3/16 (690)
Usable space in wash cabinet, width in inches (mm)	22 7/8 (580)
Usable space in wash cabinet, height in inches (mm)	20 1/8 (510)
Usable space in wash cabinet, depth of upper basket in inches (mm)	17 3/4 (450)
Usable space in wash cabinet, depth of lower basket in inches (mm)	17 3/4 (450)
In-feed height above floor in inches (mm)	8 5/16 (210)
Required niche width in mm	23 5/8 (600)
Net weight [kg]	106 (48)
Gross weight in lbs.	126 (57)
Maximum floor load in N/m ²	1000

Emission values

Emission sound pressure level in workplace (LpA)	33 dB(A) re 20 µPa
Sound power (LwA) in dB(A) re 1 pW	45.0

Programs

Universal	•
Short	•
SaniWash	•
Cold/Pre-wash	•
Glasses	•
Plastic	•
EnergySave/Economy	•
Intensive	•

Baskets

MaxiComfort P baskets	•
Flexible FlexLine basket design	•
FlexCare glass holder [number]	4
FlexCare cup rack [number]	2
Height-adjustable upper basket	•
Combinable with APFD 210 bottle basket	•
Patented 3D MultiFlex tray	•

Features

Drying	Additional drying, Active condensation drying
1 Combi dispenser/door for powder and liquid media	•
Wash cabinet made from high-quality stainless steel	•
LED Lighting	•
AutoClose	•
EcoFeedback	•
Brilliant GlassCare	•
Adjustable final rinse temperature	•
Optical interface	•

PFD 104 SCVi XXL [MAR]
Fully integrated Full-sized dishwasher with 3D MultiFlex Tray
with baskets approved by Lloyd’s Register.



EAN: 4002516424192 / Material number: 11750900 / Old Material Number: 61010415MAR	
SmartStart	•
FlexiTimer with EcoStart	•
Wi-Fi	•
Standards, test certificates, and symbols	
CE	•
Complies with Machinery Directive 2006/42/EC	•
VDE	•
EMC radio suppressed	•
DIN EN 17735	•
EN 1717	•
Lloyd’s Register	•